evision: IR Date: 9/12/08

1.0 Scope

1.1 Purpose

This procedure defines the installation procedure for the CW-172001, "Cessna 172 Vent Tube".

2.0 Applicable Documents

2.1 Federal Documents

2.1.1 AC 43.13-1B Chapter 3.

3.0 Requirements

3.1 Personnel

Installation shall be performed by qualified personnel who have been certified to perform required tasks.

3.2 Required materials for installation.

Item	

4.0 Installation Procedure

- 4.1 Removal of existing Vent Tube Adapter.
 - 4.1.1 Remove the screws from the leading edge wing root cover.
 - 4.1.2 Unhook the vent hose from old vent tube adapter.
 - 4.1.3 Remove old vent tube adapter.



This document contains confidential and proprietary information and shall not be used, cited, or reproduced without written permission from Chris Wingate

Revision: IR Date: 9/12/08

4.2 Final adjustments prior to installation

4.2.1 Take the new vent tube adapter, line the hole up with the hole on the leading edge

Note: The 1" pipe should come out level when the wing is level...if it is installed incorrectly (upside down) it will point upward at about a 45 degree angle. Make sure it is level.



4.2.2 Once everything is lined up, mark your mounting holes and drill holes oversized to allow for use of tinnerman clip
Note: Every Cosene the holes seem to be in slightly different locations.

Note: Every Cessna the holes seem to be in slightly different locations, so CW-172001 is slightly oversized to accommodate all Cessnas



This document contains confidential and proprietary information and shall not be used, cited, or reproduced without written permission from Chris Wingate rision: IR Date: 9/12/08

4.2.3 After your holes are drilled, trim excess aluminum off, but no more than necessary to allow tinnerman clip to center over the hole you just drilled.



