



# MAGNUM PREMIUM LUBRICANT WITH PTFE

The high performance lubricant specially formulated for maximum lubricity and superior protection against wear and corrosion.



## FEATURES

- High performance lubricant with PTFE additives
- Provides maximum lubrication for extreme conditions
- Penetrates and protects metal against rust, wear, and corrosion
- Extends equipment life
- Displaces Moisture
- Safe to use on most surfaces
- Flash point of 175°F(79°C)
- Nonfood Compounds Program Listed Category Code: H2 Registration #128980 (Aerosol); #128981 (Bulk)



## SPECIFICATIONS AND APPROVALS

Approved/Qualified to:

- Boise Cascade
- BMW
- General Motors Co.
- Kimberly-Clark
- New York City Transit
- PPG Glass Mfg.

## PACKAGE SIZES

### Net Contents

11 wt.oz. / 312 g/ 358 mL aerosol  
5 gal. (18.93 L)

### Part No.

00616  
00605

## APPLICATIONS

- Bearings and valves
- Cables and linkages
- Dies, bits, and fasteners
- Engines and electric motors
- Hoists, lifts, and draglines
- Metal parts and hand tools
- Parts in storage
- Production and transportation equipment
- Pulleys and rollers
- Slides and tracks



# MAGNUM

## PREMIUM LUBRICANT WITH PTFE

### PROPERTIES

Appearance /physical state	Liquid	Color	Brown
Odor	Mild, sweet	Vapor pressure	< 0.05 mmHg @ 20 °C
KB Value	Not Established	Flash point °F(°C)	175 °F (79 °C) – dispensed liquid
Boiling/condensation point °F(°C)	383 °F(195 °C)	Flash point method	Tag-Closed Cup
Specific gravity	0.85-0.87 @ 20 °C	Chemical base	Petroleum Distillates
VOC	Aerosol: 25 g/L, 2.9% per State & Federal Consumer Product Regulations Bulk: 26g/L, 3.0% per State & Federal Consumer Product Regulations	Viscosity	< 7 cSt @ 25 °C
Flammable limits (estimated)	Lower: 0.6% Upper: 7.0%	Solubility in water	< 4%
Volatiles	Not established	pH:	Not Applicable
Dielectric strength	16.3 kV	Temperature range °F(°C)	-60 °F – 300 °F (-51 °C – 149 °C)
Surface tension	Not Established	Type propellant	Carbon Dioxide
Pour point	Below -60 °F(-51 °C)	Spray pattern	Mist
HMIS 1996	1, 2, 0	NFPA	1, 2, 0
HMIS III	Aerosol: 1, 4, 2 Bulk: 1, 2, 0		

### HANDLING

DO NOT spray into or around ignition sources. DO NOT allow material to come in contact with eyes or skin. Wear appropriate protective equipment during handling. Keep container closed. Avoid breathing vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.

### STORAGE

Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store between 40 °F and 120 °F (4.4 °C and 49 °C). Protect from freezing.

Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in a dry, well-ventilated area. Avoid breathing vapors.

### DIRECTIONS

Shake well before using. Apply on clean surface when possible. Spray in even coats and reapply as needed.

### DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : [WWW.LPSLABS.COM](http://WWW.LPSLABS.COM)

**LPS® Laboratories** • An Illinois Tool Works Company  
4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899  
Internet Web Site: [www.lpslabs.com](http://www.lpslabs.com)

©2013 LPS® Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #TDS\_00616 • Rev. 12/2013