




VpCI™ METALWORKING PRODUCTS

VpCI™ -326



PRODUCT DESCRIPTION

VpCI-326 is a corrosion inhibitor oil additive for hydraulic oil and gearbox assemblies. VpCI-326 performs effectively under the adverse conditions of 100% relative humidity, and in the presence of such corrosive species as chlorides, sulfur compounds or hydrogen sulfide. VpCI-326 contains no hazardous chromates, nitrites or phosphate inhibitors.

VpCI-326 utilizes the finest paraffinic petroleum distillates as carriers. VpCI-326 possesses an exceedingly high flash point, enhancing in-plant safety when compared to common oil protectants.

VpCI-326 is supplied in concentrate form, which is easily diluted with lubricating, hydraulic or preservative oils, saving shipping and inventory expense.

VpCI-326 is a broad range corrosion inhibitor not only effective on ferrous metals, but also effective on zinc, aluminum, galvanized steel, copper, cadmium, silver, brass and many other alloys.

FEATURES

- VpCI-326 provides universal corrosion protection to ferrous and non-ferrous metals
- VpCI-326 is nitrite-free, non-toxic and thermally

stable, providing long-lasting contact and vapor phase corrosion protection

- With VpCI-326, most lubricants can be upgraded in their anti-corrosion ability providing continuous corrosion protection during operation, standby and shutdown periods
- Passes through 1 micron filter
- Conforms to MIL-PRF-46002C
- Conforms to MIL-I-85062 (Additives to oils)
- Conforms to MIL PRF-16173E
- NATO 6850-66-132-6100
- NSN 6850-01-470-3358

TYPICAL APPLICATIONS

Fog interiors with VpCI-326 concentrate at 1 liter/m³ (1 oz/ft³) of enclosed space.

VpCI-326 is not recommended for applications involving direct contact with water. Contact Cortec for application questions.

TYPICAL PROPERTIES

Appearance	Clear to slightly hazy yellow liquid
Corrosion Resistance	Up to 24 months
Coverage	960-1456 ft ² /gal (24-36 m ² /l)
Film Type	Oily, paraffinic
Film Thickness	0.5-1 mil (12.5-25 microns)
Flash Point	>230°F (>110°C)
Non-volatile Content	83-93%
pH	8.7-10.0 (1% solution)
Removal Method	Petro-solvents/alkaline cleaners (VpCI-414/416/419)
Density	7.2-7.4 lb/gal (0.86-0.89 kg/l)



CORTEC
CORPORATION

Environmentally Safe VpCI™/MCI® Technologies

PACKAGING AND STORAGE

VpCI-326 is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) metal drums, liquid totes and bulk.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  10% post consumer
Revised 5/2/06. Cortec Corporation 1999-2006. All rights reserved. Supersedes: 8/16/05.
© 1999-2006, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.