

PUSH-ON HOSE

Designed for reduced weight and increased flexibility, Phenix Push-On Hose features a Class A high oil resistant nitrile inner tube with a reinforcing two spiral aramid fiber and a nitrile/PVC cover resistant to oil and petroleum based products. Our Push-On Hose is compatible with a wide range of oils and fuels, however is NOT recommended for use with unleaded gasoline. **DO NOT USE with brake fluids or power steering fluids.**

- Operates at 250 PSI
- Temperature range: -30° to +160° F
- Compatible with Push-Lok Swivel Hose Ends

PUSH-ON HOSE BLACK



Size	Part No.	Inside Diameter	Outside Diameter	Max PSI	Min Bend Radius
-4	K204-3	0.25	0.469	250	2.5"
-6	K206-3	0.375	0.625	250	3"
-8	K208-3	0.5	0.75	250	5"
-10	K210-3	0.625	0.938	250	6"
-12	K212-3	0.75	1.03	250	7"

PUSH-ON HOSE BLUE



Size	Part No.	Inside Diameter	Outside Diameter	Max PSI	Min Bend Radius
-4	K204-4	0.25	0.469	250	2.5"
-6	K206-4	0.375	0.625	250	3"
-8	K208-4	0.5	0.75	250	5"
-10	K210-4	0.625	0.938	250	6"
-12	K212-4	0.75	1.03	250	7"

