

SRV-J Series Brochure



Camera Specifications

Model	SRV-J-1.4	SRV-J-2	SRV-J-2.8	SRV-J-4	SRV-J-6
Diameter	Φ1.4mm	Φ2.0mm	Φ2.8mm	Φ4.0mm	Φ6.0mm
Total Pixels	160000 pixels			1M pixels	1M pixels
Angle of view	100°	100°/120°		120°	90°
Depth of field	3-100mm	5-80mm			10-100mm
View direction	Forward				
Light source	Fiber optic light guide				
Probe length	8mm		10mm		13mm
Insertion tube length	1.1m			1.5m	3m
Insert tube material	Composite	Tungsten wire braided tube			
Articulation	No	360° Joystick Articulation			
Pictures/Videos	400X400	Video 400X400 - Image 720X720		1080X720	1920X1080

Features

Joystick control	Joystick Articulation 360°
Insertion tube	4-layer tungsten braided tube
LCD screen	Bright 5.0 -inch active matrix color LCD display
Key Function	Menu operation, video, photo
Image function	Graffiti, Image mirroring, zooming, preview
White balance	Automatic white balance, Adjustable Exposure
Data I/O port	USB 2.0 port, HDMI Out
Video probe operating temperature	-20 °C ~ 60 °C, below 0 °C should reduce articulation use
Relative humidity	90% max, no condensation
IP Rating	IP67
Power supply	Lithium battery: 3.7V, 4200 mAh
Data Storage	8G High Speed SD Card (up to 32G)
Storage temperature	-20°C ~ 60°C

