



Heyco® Shorty Plugs

Single Locking Step for Panel Thickness up to: .062" (1,6 mm)
 Mounting Hole Diameter Range: .187" (4,7 mm) to 1.093" (27,8 mm)


- Limited intrusion .125" (3,2 mm) inside the panel.
- Quick and easy installation.
- Multiple sizes for mounting holes from .187" (4,7 mm) to 1.093" (27,8 mm).
- Approximate Head Thickness: .062" (1,6 mm).
- For Shorty Window Plugs see page 6-36.

MOUNTING HOLE DIAMETER		PART NO.			DESCRIPTION	PART DIMENSIONS			
in.	mm.	Black	White	Colors xx*		A Head Diameter		B Overall Height	
						in.	mm.	in.	mm.
.187	4,7	2590	2591	2592xx	DP 187†	.25	6,4	.23	5,9
.218	5,5	1654	1655	1656xx	SP 218	.28	7,1	.25	6,4
.281	7,1	1660	1661	1662xx	SP 281	.34	8,7		
.307	7,8	1657	1658	1659xx	SP 307	.37	9,4		
.312	7,9	1678	1679	1680xx	SP 312	.38	9,5		
.343	8,7	1663	1664	1665xx	SP 343	.41	10,3		
.375	9,5	1681	1682	1683xx	SP 375	.47	11,9		
.390	9,9	1708	1709	1710xx	SP 390				
.406	10,3	1666	1667	1668xx	SP 406				
.437	11,1	1684	1685	1686xx	SP 437	.53	13,5		
.468	11,9	1669	1670	1671xx	SP 468				
.500	12,7	1687	1688	1689xx	SP 500	.56	14,3		
.531	13,5	1672	1673	1674xx	SP 531	.59	15,1		
.593	15,1	1675	1676	1677xx	SP 593	.69	17,5		
.625	15,9	1690	1691	1692xx	SP 625	.72	18,3		
.687	17,4	1719	1720	1721xx	SP 687	.79	20,1		
.750	19,0	1693	1694	1695xx	SP 750	.84	21,4		
.781	19,8	1696	1697	1698xx	SP 781	.89	22,6		
.875	22,2	1699	1700	1701xx	SP 875	.97	24,6		
1.000	25,4	1702	1703	1704xx	SP 1000	1.20	30,5		
1.093	27,8	1705	1706	1707xx	SP 1093	1.22	31,0		

Standard colors black or white. Consult Heyco for other colors (see below).

† Convex, glossy finish head.

*xx indicates that, following the color match process, Heyco adds a two letter suffix to the Root Part No. shown. This suffix will identify your particular CUSTOM Color selection. Consult Heyco for molded nylon color chips for accurate matching. For details as well as information regarding our Stock Colors, see page 6-53.



Quick Specs

Material
 Certifications



Nylon 6/6

Recognized under the Component Program of Underwriters' Laboratories File E51579



Certified by the Canadian Standards Association File 8919

Flammability Rating
 Temperature Range

94V-2

-40°F (-40°C) to 221°F (105°C)



Heyco® Stock and Custom* Colors for Dome Plugs and Shorty Plugs

*CUSTOM Color parts MUST be color matched. For accurate matching, consult Heyco for sample molded nylon color chips.

For complete Dome Plug Part Dimensions and Specifications, see page 6-25.

For complete Shorty Plug Part Dimensions and Specifications, see page 6-27.

- Heyco Stock and Custom Colors are Molded-in, not dyed, Colors.
- Stock and Custom Color Minimum Order Quantities are usually higher than for Black and White parts.
- **STOCK** Color means the color concentrate pellets are in stock at Heyco.
- The Stock Colors shown are **approximate**. Consult Heyco for Stock Color molded nylon color chips.
- Stock Color lead times are typically 2-3 weeks from receipt of order.
- For Stock Color part numbers in other Plug styles, for example Glossy or Double D Plugs, please consult Heyco.
- **CUSTOM** Color parts MUST be color matched to your application. For accurate matching, consult Heyco for sample molded nylon color chips.
- Custom Color lead times are typically 4 weeks from receipt of order.
- **We offer Stock and Custom Colors in virtually all of our nylon molded products.**
- Heyco’s Axcell Rapid Response Team is ready to customize your Plug in various sizes, shapes, materials, and colors. We can even mold your Company logo directly onto your Plug!

MOUNTING HOLE DIA.		PLUG TYPE	ROOT PART NO.	STOCK COLOR PART NUMBER SUFFIX										YOUR CUSTOM COLOR HERE
in.	mm.			FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX **	
.218	5,5	Shorty	1656	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.250	6,4	Dome	2605	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.281	7,1	Shorty	1662	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.312	7,9	Dome	2615	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Shorty	1680	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.343	8,7	Shorty	1665	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Dome	2619	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.375	9,5	Shorty	1683	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Dome	2635	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.437	11,1	Shorty	1686	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Dome	2645	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.500	12,7	Shorty	1689	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Dome	2645	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.531	13,5	Shorty	1674	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.562	14,3	Dome	2655	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Shorty	1692	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.625	15,9	Shorty	1692	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Dome	2675	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.687	17,4	Dome	2675	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Shorty	1695	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.750	19,1	Dome	2685	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Shorty	1695	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.812	20,6	Dome	2695	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Shorty	1701	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
.875	22,2	Dome	2705	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Shorty	1701	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
1.000	25,4	Dome	2715	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
		Shorty	1704	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
1.093-	27,8-	Dome	2725	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
1.125	28,6	Shorty	1707	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
1.187	30,1	Dome	2735	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
1.250	31,7	Dome	2742	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
1.375	34,9	Dome	2755	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
1.500	38,1	Dome	2765	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
1.750	44,5	Dome	2775	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
2.000	50,8	Dome	2785	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
2.5	63,5	Dome	2792	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	
3.0	76,2	Dome	2457	FK	FL	FJ	EH	CS	DD	CF	DQ	FI	XX	

**xx indicates that, following the color match process, Heyco will add a two letter suffix to the Root Part Number shown. This suffix will identify your particular CUSTOM Color selection. Consult Heyco for molded nylon color chips for accurate matching.



Your logo here