



FLAMEMASTERR
 Flamemaster Corp.
 13576 Desmond Street
 Pacoima, CA 91331 - USA

SAFETY DATA SHEET
 FEBRUARY 2017

File: CS3247A GSA 7-10
 Aircraft Windshield Sealant
 Base/Compound

Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

- 1.1. Product Identifier: CS-3247 Part A Class B (All)
- Product Name: Aircraft Windshield Sealant / Base compound Part-A
- Product reference: CS-3247 PT A BASE Compound

- 1.2. Product Use:**
- Aircraft Windshield Sealant

1.3. Manufacturer's Name:
CAGE Code: 14439
 Flamemaster Corp.
 Chem Seal Division
 13576 Desmond Street
 Pacoima, CA 91333 – USA

1.3.1 Suppliers Name (if not manufacturer)

Technical Contact:
 Flamemaster Corp.
 Tel: 818-890-1401
 Fax: 818-890-6001
www.flamemaster.com

1.4. Emergency Telephone:
 Chemtrec – Chemtrec International
 800-424-9300 (North America)
 703-527-3887 (Outside North America))

Specification : IAW AMS 3333A TYPE 2 Base PT A CLASS B ALL

NSN:	NONE ISSUED FOR THIS PRODUCT
-------------	-------------------------------------

Section -2. HAZARD (S) IDENTIFICATION

OSHA/HCS STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CLASSIFICATION OF THE MIXTURE:

ASPIRATION HAZARD - CATEGORY 1

SKIN SENSITIZATION - CATEGORY 1

SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A

CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION (UNBORN CHILD) - Category 2

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE - (NARCOTIC EFFECTS) - CATEGORY 3

ACUTE TOXICITY (INHALATION) - CATEGORY 4


ACUTE TOXICITY, ORAL - CATEGORY 4

ACUTE TOXICITY (DERMAL) - CATEGORY 4

AQUATIC (CHRONIC) - CATEGORY 4

GHS LABEL REQUIREMENTS

HAZARD PICTOGRAMS



SIGNAL WORD : DANGER

HAZARD STATEMENTS:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - H304

MAY CAUSE AN ALLERGIC SKIN REACTION - H317

CAUSES SERIOUS EYE IRRITATION - (H319)

CAUSES SKIN IRRITATION - (H315)

SUSPECTED OF DAMAGING THE UNBORN CHILD - (H361d)

SUSPECTED OF CAUSING CANCER - (H351)

MAY CAUSE DROWSINESS OR DIZZINESS - H336

HARMFUL IF SWALLOWED - H302

HARMFUL IN CONTACT WITH SKIN - H312

HARMFUL IF INHALED - H332

MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE - H413

PRECAUTIONARY STATEMENTS:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- Read label before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames and hot surfaces-No Smoking
- P240:Ground/bond container and receiving equipment
- P261+P262+P263+P264:Avoid breathing dust/fumes/gas/mist/vapours/spray.Do not get in eyes , on skin, or on clothing. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
- P270+P271+P273: Do not eat drink or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment.
- P281+P280: Use personal protective equipment as required. Wear protective gloves/ protective clothing/ eye protection/face protection
- P301+P310+P331: If swallowed: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.
- P305+P351+P338+P315: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Continued on Next Page

- P304+P340+P314: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell
- P342+P340+P315: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.
- P302+P352: If on skin (or in hair) : Wash with plenty of soap and water. If skin irritation occurs seek medical attention
- P306+P361: If on clothing: Remove/ take off immediately all contaminated clothing
- P402+P403+P404: Store in a dry place. Store in a well ventilated space. Store in a closed container.
- P233+P234+P235: Keep container tightly closed. Keep only in original container. Keep cool.

SUPPLEMENTAL LABEL ELEMENTS:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of concentrations above recommended limits causes headaches, drowsiness and nausea and could lead to unconsciousness or possibly death.

1-component mixtures: formaldehyde is released during the curing phase. Formaldehyde may cause irreversible effects, is irritating to the mucous membranes and may cause the skin to become sensitized.

Avoid any contact with skin or clothing and wash thoroughly after handling.

Emits toxic fumes when heated.

HAZARDS NOT OTHERWISE CLASSIFIED:

Prolonged or repeated exposure may dry skin and / or cause skin irritation.

Sanding and grinding dust may be harmful if inhaled. Sanding and grinding dust may form combustible concentrations in air.

Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

GHS CLASSIFICATION:LIQUID POLYMER - NOT CLASSIFIED

GHS CLASSIFICATION:LIQUID POLYMER - NOT CLASSIFIED

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS): TOLUENE

FLAMMABLE LIQUIDS (CATEGORY 2),H225

SKIN IRRITATION (CATEGORY 2),H315

REPRODUCTIVE TOXICITY (CATEGORY 2),H361

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE-(CATEGORY 3),CENTRAL NERVOUS SYSTEM,H336

SPECIFIC TARGET ORGAN TOXICITY-REPEATED EXPOSURE (CATEGORY 2),H373

ASPIRATION HAZARD (CATEGORY 1),H304

ACUTE AQUATIC TOXICITY (CATEGORY 2),H401

CALCIUM CARBONATE:

GHS CLASSIFICATION: CALCIUM CARBONATE - NOT CLASSIFIED

CARBON BLACK

MAY FORM COMBUSTIBLE DUST CONCENTRATIONS IN AIR

Bisphenol A- Epoxy Resin with Toluene

FLAMMABLE LIQUIDS - CATEGORY 2

SKIN CORROSION/IRRITATION - CATEGORY 2

SERIOUS EYE DAMAGE/EYE IRRITATION - CATEGORY 2A

SKIN SENSITIZATION - CATEGORY 1

TOXIC TO REPRODUCTION (UNBORN CHILD) - CATEGORY 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (NARCOTIC EFFECTS) - CATEGORY 3

AQUATIC HAZARD (ACUTE) - CATEGORY 2

AQUATIC HAZARD (LONG TERM) - CATEGORY 3

SUBSTANCE % by weight in the product	H&P STATEMENTS	CAS	EINECS/ELINCS
LIQUID POLYMER < 70%	NOT CLASSIFIED	N/A	POLYMER
LIQUID POLYMER < 70%	NOT CLASSIFIED	N/A	POLYMER
TOLUENE (Methylbenzene) < 5%	H225,H304,H315,H319,H332,H336, H361,H371,H401, P210P260,P281,P301+P310,P305+ P351+P338,P331	108-88-3	203-625-9
CARBON BLACK <5%	May form combustible dust concentrations in air	1333-86-4	N/A
Calcium Carbonate <45%	NOT CLASSIFIED	72608-12-9	207-439-9
Bisphenol A- Epoxy Resin with Toluene <3%	H225, H319, H315, H317, H361d, H336, H400, H412	N/A	N/A

Section -4. FIRST-AID MEASURES

General: When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Eye contact: Remove any contact lenses if present and easy to do. Irrigate with clean, fresh water for at least 15 minutes, holding the eye lids apart, and seek immediate medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

Section -5. FIRE-FIGHTING MEASURES

Extinguishing agents

Recommended: Universal resistant foam, CO₂, water, powder.

Agents to avoid: None known

Attention

Promptly remove all persons in the event of a fire from the fire area. If safe to do so, remove all containers from fire area as well.

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

HAZARDOUS DECOMPOSITION PRODUCTS INCLUDE BUT MAY NOT BE LIMITED TO THE FOLLOWING:

- | | |
|-------------------|---|
| • Carbon Monoxide | • Halogenated Compounds |
| • Sulfur Oxides | • Oxides of Carbon,Nitrogen,Sulfur Dioxide,Trace Hydrogen Sulfide |
| • Carbon Dioxide | • Metal Oxide / Oxides |
| • Formaldehyde | • Smoke |
| • Toxic Fumes | • Organic Compounds |
| • Smoke | • Other hazardous compounds |

In case of inhalation of decomposition products released in a fire, symptoms may be delayed. Exposed persons may need to be kept under medical surveillance for at least 48 hours.

Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Section -7. HANDLING AND STORAGE

7.1 Handling:

No smoking, eating and drinking during handling. Wash hands and face before eating, drinking, or smoking.

Avoid exposure during pregnancy/while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Continued on Next Page

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

7.2 Storage:

Observe label precautions. Store between 32/F and 95/F (0/C and 35/C) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

8.2 Exposure limits

Work place exposure limits (8 hour)

Substance	OSHA	ACGIH TWA
LIQUID POLYMER	Not known	Not known
LIQUID POLYMER	Not known	Not known
TOLUENE (Methylbenzene)*	200 ppm	20 ppm
CALCIUM CARBONATE *	5 mg/m ³ (RESPIRABLE FRACTION)	3 mg/m ³ (RESPIRABLE FRACTION)
CALCIUM CARBONATE *	15mg/m ³ (TOTAL DUST)	10 mg/m ³ (TOTAL DUST)
CARBON BLACK *	3.5 mg/m ³	3.0 mg/m ³
* can be absorbed through skin		

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

Continued on Next Page

Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

9. PHYSICAL AND CHEMICAL PROPERTIES

- | | |
|--|--|
| <ul style="list-style-type: none"> • Physical state at: 68 ° F (20 ° C) Liquid • Flash point: 200 ° F (93 ° C) Method: TCC • Specific gravity at: 68 ° F (20 ° C) 1.52 g/cm³ • Vapor Density: NIL • Lower Explosive Limit (% vol.): N/A • Upper Explosive Limit (% vol.): N/A • Miscibility in water at 20 ° C: NEGLIGIBLE | <ul style="list-style-type: none"> • Ph : 8.5 • Volatile by Volume % : 3.0 • Vapor pressure at: 68 ° F (20 ° C) NIL • Color: Off white to white • Appearance: Paste • Odor: Polysulfide Odor • Boiling Point: N/A |
|--|--|

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products including but not limited to the following:

- | | |
|--|--|
| <ul style="list-style-type: none"> • Carbon Monoxide • Sulfur Oxides • Carbon Dioxide • Formaldehyde • Toxic Fumes • Smoke | <ul style="list-style-type: none"> • Halogenated Compounds • Oxides of Carbon, Nitrogen, Sulfur Dioxide, Trace Hydrogen Sulfide • Metal Oxide / Oxides • Smoke • Organic Compounds • Other hazardous compounds |
|--|--|

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs of overexposure include headache, dizziness, fatigue, muscular weakness, drowsiness, reduced fetal weight, increase in fetal deaths, skeletal malformations, and in extreme cases loss of consciousness

Repeated or prolonged contact with the preparation may cause Defatting of the skin resulting in non-allergic dermatitis and absorption through the skin.

The liquid splashed in the eyes causes serious eye irritation and damage.

Irritating to mouth, throat and stomach. Ingestion causes reduced fetal weight, increased fetal deaths and skeletal malformations

Formaldehyde is released during curing.

Emits toxic fumes when heated.

ACUTE TOXICITY:

PRODUCT:	RESULT	SPECIES	DOSE	EXPOSURE
Calcium Carbonate Toluene	LD50 ORAL	Rat	6450 mg/kg	-
	LC50 Inhalation Vapor	Rat	49 g/m ³	4 Hours
	LC50 Inhalation Vapor	Rat	8000 ppm	4 Hours
	LD50 Dermal	Rabbit	8.39 g/kg	-
	LD50 ORAL	Rat	636 mg/kg	-
Bisphenol A- Epoxy Resin	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 ORAL	Rat	>2000 mg/kg	-
Carbon Black	LD50 Oral	Rat	>8000 mg/kg	-

CARCINOGENICITY:

INGREDIENT	IARC	OSHA	NTP	CAS#
TOLUENE :	3	-	-	108-88-3
Carbon Black	2B	-	-	1333-86-4

SPECIFIC TARGET ORGAN TOXICITY-STOT (SINGLE EXPOSURE)

TOLUENE - CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY-STOT (REPEATED EXPOSURE)

TOLUENE - CATEGORY 2

TARGET ORGANS: BRAIN, BLOOD, KIDNEYS, LUNGS, REPRODUCTIVE SYSTEM, LIVER, HEART, PERIPHERAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, UPPER RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS AND/OR CORNEA.

ASPIRATION HAZARD:

TOLUENE - CATEGORY 1

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS - H304

MAY CAUSE AN ALLERGIC SKIN REACTION - H317

CAUSES SERIOUS EYE IRRITATION - (H319)

CAUSES SKIN IRRITATION - (H315)

SUSPECTED OF DAMAGING THE UNBORN CHILD - (H361d)

SUSPECTED OF CAUSING CANCER - (H351)

MAY CAUSE DROWSINESS OR DIZZINESS - H336

HARMFUL IF SWALLOWED - H302

HARMFUL IN CONTACT WITH SKIN - H312

HARMFUL IF INHALED - H332

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Toxicity :

Product / Ingredient	Result	Species	Exposure
Carbon Black	LC50 >1000 mg/L	Brachydanio Rerio	96 Hours
	EC50 >5600 mg/L	Daphnia Magna	24 Hours
	EC50 >10000 mg/L	Algae	72 Hours
	NOEC >=10000 mg/L	Algae	-
	EC0 >=800 mg/L	Activated Sludge	3 Hours

Persistence and Degradability :

Product / Ingredient	Aquatic Half Life	Photolysis	Biodegradability
Toluene	-	-	Readily (5 days - 81 %)
bisphenol A - epoxy resins	-	-	Not Readily Biodegradeable (28 days - 5%)

Bioaccumulative Potential :

Product / Ingredient	LogP(ow)	BCF	Potential
Toluene	2.73	8.32	low
bisphenol A - epoxy resins	-	31	low

Mobility in Soil : Not Available

13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with curing agent and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

14. TRANSPORT INFORMATION

DOT: Not regulated

UN Number: Not regulated

IATA: Not regulated

IMDG/IMO: Not regulated

NMFC: 4620 SUB.5 – CL.60

Schedule B # 3506.91.0000

15. REGULATORY INFORMATION

US Regulations Federal

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit (Reporting Value)
	TOLUENE (Methylbenzene)	108-88-3	<5%	Unknown

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

US Regulations State

California Proposition 65 (Developmental – Female)	TOLUENE	108-88-3	<5%	>= 1.0%
Massachusetts	TOLUENE	108-88-3	<5%	>= 1.0%
New Jersey	TOLUENE	108-88-3	<5%	>= 1.0%
Pennsylvania	TOLUENE	108-88-3	<5%	>= 1.0%
Rhode Island	TOLUENE	108-88-3	<5%	>= 1.0%
California Proposition 65 (Developmental – Female)	Carbon Black	1333-86-4	<5%	>=1.0%
Massachusetts	Carbon Black	1333-86-4	<5%	>= 1.0%
New Jersey	Carbon Black	1333-86-4	<5%	>= 1.0%
Pennsylvania	Carbon Black	1333-86-4	<5%	>= 1.0%

Toluene: Fire Hazard, Immediate (acute) Health Hazard, Delayed (chronic) Health Hazard

Bisphenol A -Epoxy Resins with Toluene: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health hazard

Carbon Black: Chronic Health Hazard, Fire Hazard

Sudden Release Of Pressure: No Products

Reactivity: No Products

California Prop. 65 : Warning

This product contains a chemical or chemicals known by the State of California to cause cancer, birth defects, or other reproductive harm.

Canada



Class B – Flammable
TOLUENE



Class D - Poisonous and Infectious
materials Division 2: Materials Causing
Other Toxic Effects D2A D2B
TOLUENE CAS# 108-88-3
Carbon Black CAS# 1333-86-4
Calcium Carbonate CAS# 72608-12-9
Bisphenol A -Epoxy Resins Cas#6794-34-9

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Listed National Pollutant Release Inventory (NPRI):
Bisphenol A -Epoxy Resins Cas# 67924-34-9
Toluene Cas# 108-88-3

16. OTHER INFORMATION

HEALTH	1	
FLAMMABILITY	1	Customer and / or end user is responsible
REACTIVITY	0	for determining PPE.

HMIS

Preparer:	Flamemaster / Compliance Rev-A 4/02/2015 Supersedes (conversion)	Revision Notes: A	Conversion to ANSI format
Containers:	plastic jars, metal cans cartridge kits		
Limited Quantity	See SDS Section 14		
Maximum container size	50 Gallons / 190 Liters		

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

End of Safety Data Sheet



FLAMEMASTER
 Flamemaster Corp.
 13576 Desmond Street
 Pacoima, CA 91331 - USA

SAFETY DATA SHEET
 FEBRUARY 2017

File: CS3247BB GSA 07-10
 Aircraft Windshield
 Sealant/Catalyst

Section -1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1. Product Identifier: CS-3247 Part B Class B (all application times)
 - Product Name: Aircraft Windshield Sealant / Catalyst Part B
 - Product reference: CS-3247-B

1.2. Product Use:
 -Aircraft Windshield Sealant

1.3. Manufacturer's Name:
 CAGE Code: 14439
 Flamemaster Corp.
 Chem Seal Division
 13576 Desmond Street
 Pacoima, CA 91333 – USA

1.3.1 Suppliers Name (if not manufacturer)

Technical Contact:
 Flamemaster Corp.
 Tel: 818-890-1401
 Fax: 818-890-6001
www.flamemaster.com

1.4. Emergency Telephone:
 Chemtrec – Chemtrec International
 800-424-9300 (North America)
 703-527-3887 (Outside North America))

Specification: IAW AMS 3333A Catalyst Part B CLASS B (ALL)

NSN:	NONE ISSUED FOR THIS PRODUCT
-------------	-------------------------------------

Section -2. HAZARD (S) IDENTIFICATION

ASPIRATION HAZARD 1, H304

ACUTE TOXICITY (ORAL) 4, H302

ACUTE TOXICITY (INHALATION) 4, H332

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2

SKIN CORROSION/IRRITATION - Category 2

SKIN SENSITIZATION 1, H317

CARCINOGENICITY 2, H351

TOXIC TO REPRODUCTION (FERTILITY) 2, H361f

SPECIFIC TARGET ORGAN TOXICITY (STOT) REPEATED EXPOSURE 2, H373

AQUATIC CHRONIC 4, 413

For A Complete List of H-Statements and Classifications See Section 16

OSHA / HCS STATUS : THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

Human and Environmental Hazards:

HAZARD STATEMENTS:

May Be Fatal If Swallowed and Enters Airways.

Harmful by Inhalation and / or Swallowing

Causes Serious Eye Irritation

Causes Skin Irritation

May Cause An Allergic Skin Reaction


Suspected of Causing Cancer

Suspected of Damaging Fertility

May Cause Damage to Organs Through Prolonged or Repeated Exposure

May Cause Long Lasting Harmful Effects to Aquatic Life

HAZARD PICTOGRAMS:



SIGNAL WORD:

DANGER

Full text of P statements associated to this compound:

- P101+P102+P103: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
- Read label before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames and hot surfaces-No Smoking
- P240:Ground/bond container and receiving equipment
- P261+P262+P263+P264:Avoid breathing dust/fumes/gas/mist/vapours/spray.Do not get in eyes , on skin, or on clothing. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
- P270+P271+P273: Do not eat drink or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment.
- P281+P280: Use personal protective equipment as required. Wear protective gloves/ protective clothing/ eye protection/face protection
- P301+P310+P331: If swallowed: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.
- P305+P351+P338+P315: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,if present and easy to do. Continue rinsing. Get immediate medical advice attention.
- P304+P340+P314: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell
- P342+P340+P315: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.

- P302+P352: If on skin: Wash with plenty of soap and water
- P306+P361: If on clothing: Remove/ take off immediately all contaminated clothing
- P402+P403+P404: Store in a dry place. Store in a well ventilated space. Store in a closed container.
- P233+P234+P235: Keep container tightly closed. Keep only in original container. Keep cool.

HAZARDS NOT OTHERWISE CLASSIFIED: OXIDISING POTENTIAL: Contact with combustible material may result in fire. Keep away from combustible materials. This material increases the risk of fire and may aid in combustion.

Other Hazards that do not result in classification:

Prolonged or repeated exposure may dry skin and / or cause irritation

Section -3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family : Mixture of organic compounds

For the hazards of the composition, (SDS see Section 2).

CHEMICAL NAME: MANGANESE DIOXIDE OSHA HAZARDS: TARGET ORGAN EFFECT, TOXIC BY INHALATION TARGET ORGANS: NERVES, LUNGS GHS CLASSIFICATION: ACUTE TOXICITY, ORAL (CATEGORY 4) - H302 ACUTE TOXICITY, INHALATION (CATEGORY 4) - H332	CAS# 1313-13-9	EC# 215-202-6	<65% by weight
CHEMICAL NAME: TERPHENYL, HYDROGENATED AQUATIC CHRONIC (CATEGORY 4) - H413	CAS# 61788-32-7	EC# 262-967-7	<50% by weight
CHEMICAL NAME: ZEOLITES NOT CLASSIFIED	CAS# 1318-02-1	EC# 215-283-8	<15% by weight
CHEMICAL NAME: TALC NOT CLASSIFIED	CAS# 14807-96-6	EC# 238-877-9	<10% by weight
CHEMICAL NAME: CARBON BLACK NOT CLASSIFIED	CAS# 1333-86-4	EC# 215-609-9	<10% by weight
CHEMICAL NAME: TERPHENYL AQUATIC ACUTE (CATEGORY 1) - H400 AQUATIC CHRONIC (CATEGORY 1) - H410	CAS# 26140-60-3	EC# 247-477-3	<10% by weight
CHEMICAL NAME: 1,3 DIPHENYLGUANIDINE ACUTE TOXICITY (CATEGORY 4) - H302 SKIN IRRITATION (CATEGORY 2) - H315 EYE IRRITATION (CATEGORY 2) - H319 REPRODUCTIVE (CATEGORY 2) - H361f (FERTILITY) STOT-SINGLE EXPOSURE (CATEGORY 3) - H335 AQUATIC CHRONIC (CATEGORY 2) - H411	CAS# 102-06-7	EC# 203-002-1	<3% by weight
CHEMICAL NAME: BIS(PIPERIDINOTHIOCARBONYL) TETRASULFIDE SKIN SENSITIVITY (CATEGORY 1) - H317	CAS# 120-54-7	EC# 204-406-0	<3% by weight
CHEMICAL NAME: POLYPHENYL, QUATER AND HIGHER	CAS# 68956-74-1		<10% by weight
MAGNESIUM CARBONATE	CAS# 546-93-0		<10% by weight

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

Section -4. FIRST-AID MEASURES

General: When in doubt or symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, if breathing has stopped, administer artificial respiration. Give nothing by mouth, seek immediate medical attention.

Eye contact: Check for and remove any contact lenses. Irrigate with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek immediate medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use aromatic solvents, thinners or petroleum products.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

May be fatal if swallowed or vomited and enters lungs and/or airways. Never give anything by mouth to an unconscious person.

Section -5. FIRE-FIGHTING MEASURES

Extinguishing agents

Recommended: Universal resistant foam, CO₂, water, powder.

Agents to avoid: None known

Attention

Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.

Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.

Do not weld, flame cut or expose to extreme heat or ignition sources, empty containers which have contained flammable products.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Hazardous decomposition products include: Carbon Dioxide, Carbon Monoxide, Nitrogen Oxides, Sulfur Oxides

Metal Oxide / Oxides, Manganese Compounds, Smoke, Other Toxic / Noxious Fumes

Section -6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition, ventilate the area. Avoid breathing vapors by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.

Collect spill with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean-up with a detergent/ water mix ; avoid use of aromatic solvents. If the product enters drains or watercourses, inform authority with jurisdiction in accordance with state / local regulations.

Section -7. HANDLING AND STORAGE

7.1 Handling:

No smoking, eating and drinking during handling.

Avoid exposure during pregnancy / while nursing.

Keep containers tightly closed. Prior to movement containers which are opened should be carefully resealed.

Avoid skin and eye contact. Avoid inhalation in case of exposure to vapor and spray mist.

Handle and open containers with care to avoid spilling of contents. Never use pressure to empty; container is not a pressure vessel. Clean or discard contaminated clothing and shoes.

Preparation may charge electrostatically; always use grounding/ bonding/ earthing leads when transferring contents of containers. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air, and avoid vapor concentration higher than the Occupational Exposure Limits.

Use in areas from which local sources of ignition have been excluded. Electrical equipment including lighting should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. Non-sparking tools are recommended.

7.2 Storage:

Observe label precautions. Store between 32/F and 95/F (0/C and 35/C) in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight. For flash points below 23 °C store in an area constructed to the appropriate standard

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Engineering measures:

Avoid the inhalation of vapors, spray mist and particulates. Achieve by local exhaust ventilation providing good general extraction as to keep air-borne concentration below the Occupational Exposure Limits (OEL).

If local / area ventilation is not sufficient to comply with OEL, suitable (NIOSH) respiratory protection to be provided. Always provide suitable (NIOSH) respiratory protection when sanding, grinding or otherwise abrading cured material.

8.2 Exposure limits

Work place exposure limits (8 hour)

Substance	ACGIH TLV
Manganese Dioxide	TWA: 0.1mg/m ³ (as Mn) 8 hours (Inhalable Fraction)
	TWA: 0.02mg/m ³ (as Mn) 8 hours (Respirable Fraction)
Terphenyl, Hydrogenated	TWA: 4.9 mg/m ³ 8 hours
	TWA: 0.5 ppm 8 hours
Zeolites	TWA: 1mg/m ³ 8 hours (Respirable Fraction)
Talc	TWA: 2mg/m ³ 8 hours (Respirable Fraction)
Carbon Black	TWA: 3mg/m ³ 8 hours (Inhalable Fraction)
Terphenyl	C: 5mg/m ³
	C: 0.53 ppm
MAGNESIUM CARBONATE	TWA: 5mg/m ³ (Respirable Fraction)
	TWA: 15 mg/m ³ 8 hours (Total Dust)

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protection, used to control exposure to hazardous substances must be selected to meet the requirements of OSHA Regulations.

Respiratory protection :

Appropriate respiratory protection equipment should be selected according to the type of contaminants, following regulatory (OSHA / NIOSH) and manufacturers instructions including proper fitting of devices.

Hand protection :

For prolonged or repeated contact, recommend gloves type: polyvinyl alcohol, nitrile rubber, latex rubber (some people may exhibit sensitivity to Latex). Barrier creams may help to protect exposed areas of the skin. However, they should not be applied post exposure.

Eye protection :

Use safety glasses with side shields to protect against splashes. Face shields may also be worn.

Skin protection :

Protective clothing made of antistatic and fire resistant fibers. All parts of the body should be washed after contact. Use good hygiene and industrial practices, keep working clothes clean.

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state at: 68 ° F (20 ° C) Liquid
 - Flash point: 200 ° F (93 ° C) Method: TCC
 - Specific gravity at: 68 ° F (20 ° C) 2.0
 - Vapor Density: N/A
 - Lower Explosive Limit (% vol.): N/A
 - Upper Explosive Limit (% vol.): N/A
 - Miscibility in water at 20 ° C: NEGLIGIBLE
 - Material Supports Combustion. : Yes
- Ph : 9.0
 - % VOLATILE BY VOLUME - 2.0
 - Vapor pressure at: 68 ° F (20 ° C) N/A
 - Color: BLACK
 - Appearance: PASTE
 - Odor: NEGLIGIBLE OILY ODOR
 - Boiling Point: 360° C (680° F)

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see SDS section 7). In case of combustion, may produce hazardous decomposition products such as :

- Carbon monoxide
- Sulfur oxides
- Carbon Dioxide
- Oxides of nitrogen
- Metal Oxide / Oxides
- Manganese Compounds
- Smoke
- Toxic Fumes / Noxious fumes

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. See (SDS Sections 3 and 15) for details.

Exposure to component solvents vapors at concentrations in excess of the stated Occupational Exposure Limits may result in adverse health

ACUTE TOXICITY:

PRODUCT:	RESULT	SPECIES	DOSE	EXPOSURE
Manganese Dioxide	LD50 ORAL	Rat	3478 mg/kg	-
Terphenyl, Hydrogenated	LD50 ORAL	Rat	17500 mg/kg	-
Zeolites	LD50 ORAL	Rat	>5 g/kg	-
Carbon Black	LD50 Dermal	Rabbit	>3 g/kg	-
	LD50 Oral	Rat	>15400mg/kg	-
Terphenyl	LD50 Oral	Rat	>1400 mg/kg	-
Magnesium Carbonate	LD50 Oral	Rat	8000mg/kg	-
1, 3-Diphenylguanidine	LD50 Oral	Rat	323mg/kg	-

CARCINOGENICITY:

INGREDIENT	IARC	OSHA	NTP
Zeolites	3	-	-
Carbon Black, Respirable Powder	2B	-	-

Specific Target Organ Toxicity (STOT)- Single Exposure

1,3-Diphenylguanidine - (Category 3)

Zeolites - (Category 3)

Talc - (Category 3)

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

This Product is Harmful if Swallowed or Inhaled.
This Product also Causes Serious Eye Irritation.
This Product Causes Skin Irritation, Defatting of the Skin, and May Cause an Allergic Reaction.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Manganese Dioxide - (Category 2)

Potential chronic health effects include the following:

May cause damage to organs through prolonged or repeated exposure. May lead to defatting of the skin and / or irritation.
May lead to allergic reactions.
Suspected of causing cancer.
Suspected of damaging fertility

Target Organs: lungs, skin, central nervous system, blood, kidneys, nervous system, liver, spleen, lymphatic system, cardiovascular system, upper respiratory tract, bone marrow, eye, lens, cornea

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself. Do not allow the product to enter drains or water ways. See (SDS Sections 3 and 15)

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

Bioaccumulative Potential:

Product	LogPow	BCF	Potential
1,3 Diphenylguanidine	1.69	19.95	Low
Bis(piperidinothiocarbonyl) tetrasulfide	2.8	16.98	Low

Mobility in Soil:

Not Available

13. DISPOSAL CONSIDERATIONS

Recommended incineration or land fill as hazardous waste per Federal, State and local regulations.

React with base and dispose of as hazardous waste per Federal, State and local regulations. Recommended incineration or land fill.

Empty containers and/or liners may contain material residue. Empty contaminated packagings thoroughly. Dispose in accordance with all Federal, State, and local health and environmental regulations.

Never allow this material, any solutions, or any by-products, as well as any run-off, to come into contact with soil, waterways, wildlife habitats, drains, sewers, and / or the ocean. Avoid release into environment.

14. TRANSPORT INFORMATION

DOT: Not regulated

UN Number: Not regulated

IATA: Not regulated

IMDG/IMO: Not regulated

NMFC: 4620 SUB.5 – CL.60

Schedule B # 3506.91.0000

15. REGULATORY INFORMATION

Other EU Regulations:

1,3-Diphenylguanidine - Reproductive (Category 2) H361f (Fertility)

SARA 311/312

Classification: Immediate (acute) health hazard

Delayed (chronic) health hazard

Composition of Ingredients :

Manganese Dioxide : Immediate (acute) health hazard
Delayed (chronic) health hazard

Zeolites : Immediate (acute) health hazard

Polyphenyls, quater and higher : Immediate (acute) health hazard

Talc : Immediate (acute) health hazard

Carbon Black : Fire Hazard
Delayed (chronic) health hazard

Terphenyl : Immediate (acute) health hazard

1,3-Diphenylguanidine : Fire Hazard
Immediate (acute) health hazard
Delayed (chronic) health hazard

Bis(piperidinothiocarbonyl) : Fire Hazard
tetrasulfide Immediate (acute) health hazard

US Regulations Federal

chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 (SARA)	Chemical Name	CAS No	Weight %	Threshold limit (Reprting Value)
	Manganese Dioxide	1313-13-9	<65%	Unknown

SARA notifications must remain attached to this SDS. Any copies and /or distribution of this SDS must include all SARA notifications.

All remaining Constituents are non-hazardous per FED-STD-313 All Constituents are listed in TSCA inventory; complete mixture is excluded Per TSCA Par. 710.4 (d) 95 (6) (7) Constituents are not listed in TSCA 12b CORR. LIST

US Regulations State

California Proposition 65 (Developmental – Female)	MANGANESE DIOXIDE	1313-13-9	< 65%	>= 1.0%
Massachusetts	MANGANESE DIOXIDE	1313-13-9	< 65%	>= 1.0%
New Jersey	MANGANESE DIOXIDE	1313-13-9	< 65%	>= 1.0%
Pennsylvania	MANGANESE DIOXIDE	1313-13-9	<65%	>= 1.0%
Rhode Island	MANGANESE DIOXIDE	1313-13-9	<65%	>= 1.0%

California Prop 65 Warning :

This Product contains one or more ingredients known by the state of California to cause cancer.



materials Division 2: Materials Causing Other Toxic Effects:
Manganese Dioxide CAS#1313-13-9

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR. Listed National Pollutant Release Inventory (NPRI):Manganese Dioxide cas#1313-13-9

HEALTH 3
FLAMMABILITY 1
REACTIVITY 1

HEALTH 3
FLAMMABILITY 1
REACTIVITY 1

Customer and / or end user is responsible for determining PPE.

NFPA

HMIS

This sds is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling,storage,use and disposal are beyond our control and may be beyond our knowledge.

Section 16 Other Information

Full Text of H Statements Associated with this Compound:

ASPIRATION HAZARD 1, H304
ACUTE TOXICITY (ORAL) 4, H302
ACUTE TOXICITY (INHALATION) 4, H332
SKIN SENSITIZATION 1, H317
CARCINOGENICITY 2, H351
TOXIC TO REPRODUCTION (FERTILITY) 2, H361f
SPECIFIC TARGET ORGAN TOXICITY (STOT) REPEATED EXPOSURE 2, H373
AQUATIC CHRONIC 4, H413

H304 - MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

H302 - HARMFUL IF SWALLOWED.

H332 - HARMFUL IF INHALED.

H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.

H351 - SUSPECTED OF CAUSING CANCER.

H361f - SUSPECTED OF DAMAGING FERTILITY.

H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

H413 - MAY CAUSE LONG LASTING HARMFUL EFFECTS TO AQUATIC LIFE.

Preparer-Flamemaster/Compliance
Rev A April 2015
Supercedes(Conversion)

Revision Notes: A

Conversion to ANSI format

Containers: Plastic Jars, Metal Cans, Cartridge Kits

Maximum Container Size: 50 Gallons/190 Liters

Notice to reader:

This SDS is provided without any warranty expressed or implied regarding its correctness or suitability for specific situations. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge.

In all cases, the user must determine the applicability of all information and recommendations contained herein as well as the suitability of this product for their own particular needs or purposes.

This product may be hazardous and should always be used with care and discretion. Every effort has been made to describe all known hazards, but this in no way guarantees the above mentioned hazards are the only hazards present.

Flamemaster Corporation, its Affiliates and its Agents, shall in no way be held liable for any damages resulting from handling, using, storing, disposing of, or from contact with this product. User assumes all risk.

END OF SAFETY DATA SHEET