

# KX 200 NAVIGATION/ COMMUNICATION RADIO

Meet the Next-Generation Honeywell KX 200 NAV/COM Radio



**Honeywell**

# KX 200 NAVIGATION/ COMMUNICATION RADIO

## Meet the Next-Generation Honeywell KX 200 NAV/COM Radio

### DEVELOPED WITH PILOTS

General aviation's newest and most advanced NAV/COM radio is pilot-friendly by design. That's because we consulted pilots at every phase of a development process that started with a blank CAD screen and ended with the creation of a groundbreaking new radio for the 2020s and beyond.

The Honeywell KX 200 is an easy direct replacement with the same footprint as your current KX 155 radio. But that is where the similarity ends.

### Honeywell Makes Upgrading to the KX 200 Easy

Moving up to the KX 200 couldn't be easier, since it's a direct replacement for your current KX 155 and can substitute other radios using the same tray and connector.

That also means the KX 200 is compatible with existing equipment, which reduces both cost and aircraft downtime during the conversion.

### FEATURES:

- High-resolution color LCD
- 50-channel memory presets
- 25kh or 8.33kh channel spacing
- Full featured digital NAV/COM with VOR, LOC, ILS, and glide slope
- Compatible with existing indicators and installed equipment
- Compatible with 14- and 28-volt systems
- Possibility to expand capabilities with future Honeywell Anthem™ cockpit connectivity
- Two-year warranty



## KX 200 NAV/COM TECHNICAL DATA

GENERAL SPECIFICATION	
Supply Voltage	14 and 28 Volt system
Current consumption	≤ 750 mA @ 12V; RX RX stand-by mode ≤ 400 mA @ 28 VDC; RX stand-by mode ≤ 2.5 A @ 12 VDC; TX mode (m ≥ 70%, 1 kHz) ≤ 1.8 A @ 28 VDC; TX mode (m ≥ 70%, 1 kHz)
Operating temperature	-20...+55 °C
Control interface	COM: RS422 NAV: RS422
Dimensions HxWxD (install. Depth)	52.1 x 158.8 x 224 mm (2.1 x 6.3 x 8.8 inch)
Weight	≤ 1.5 kg
COM TRANSCEIVER	
Number of channel memory	50 + 10 Last
Channel labeling	Yes
<b>Receiver</b>	
Frequency range	118.000- 136.991666 MHz
Channel spacing	8.33 / 25 kHz
Modulation	AM
Audio frequency response	350...2500 Hz @ 8.33 kHz channel spacing 350...3000 Hz (typically 300...3400 Hz) @ 25 kHz channel spacing
Sensitivity	≤ -93 dBm (typically -101 dBm) for AM 30%, 1000 Hz
Spurious response	≥ -33 dBm
Dual watch (SCAN)	Yes
Climax operation	YES, Class H2 receiver
Frequency change notification	Yes
Squetch threshold	6...26 dB
Single / multicarrier distortions	≤ 25% (typically ≤ 15%) for AM 85%
<b>Transmitter</b>	
Transmitting power	≥ 6 W @ 14 VDC, ≥ 10 W @ 28 VDC
Modulation capability	≥ 70%, ≤ 95%
Frequency stability	better than ± 5 ppm
Modulated audio distortion	≤ 15%
Modulated audio response	350...2500 Hz
Stuck PPT	35 s
NAV RECEIVER	
NAV channels	108.00 ... 117.95 MHz
Number of channel memory	50 + 10 Last
NAV sensitivity	-93 dBm, -107 Dbm (typically)
VOR/LOC output	Composite signal for external VOR/LOC converter and indicator
Auxiliary power supply output	up 500 mA
ILS energize output	Open collector to ground discrete output
DME channeling	Serial DME channeling provided for KN 62A, KN 63, KN 64
NAV audio output power	≥ 100 mW @ 500 Ω, ≥ 100 mW @ 600 Ω
IDENT notch filter	ON/OFF
GS channels	329.15...335.00 MHZ

**Find out more**

To learn more, call 1.855.250.7027  
to contact your local  
Honeywell dealer  
or visit us online

**Honeywell Aerospace Technologies**

21111 N 19th Avenue,  
Phoenix, Arizona 85027-2708  
[aerospace.honeywell.com](http://aerospace.honeywell.com)

N61-3170-000-001 | 05/24  
© 2024 Honeywell International Inc.

**THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT**

**Honeywell**