



GENERAL SPECIFICATIONS	
VOLTAGE INPUT RANGE	8.5 - 30.0 V _{DC}
OPERATING INPUT CURRENT REQUIREMENT	0.25 A MAX
P-LEAD INPUT SOURCE	SUREFLY IGNITION MODULE
0 - 5 V _{DC} SQUARE WAVE OUTPUT	5 V _{DC} WAVE FORM 50% DUTY CYCLE 6K OUTPUT IMPEDENCE 1 PULSE/REV 4-CYL 1.5 PULSE/REV 6-CYL
HORIZON TACHOMETER OUTPUT	-10 V _{DC} PULSE 1.6ms DURATION 1K OUTPUT IMPEDENCE

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED

SureFly Granbury, Texas				
TACH2 SIGNAL CONVERTER				
SCALE: 1:1	MATERIAL: N/A	FINISH: N/A		
DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED		DRAWN BY: R. CONDY	DATE: 09/01/2019	
TOLERANCES:			SHEET: 1/1	PART NO: TACH2
ANGLES ±1°	0.X ±0.050	0.XX ±0.030	0.XXX ±0.010	REV: IR