

HA

AN Bolts

- Made of high-strength type 4037 or 8740 alloy steel
- Centerless ground & threaded
- Minimum tensile strength 125,000 PSI
- Cadmium plated per spec QQ-P-416A, Type II, Class 3
- 431 Stainless steel (CRES)







UNDRILLED

NO LETTER EXAMPLE! AN6 - 10

FOR DRILLED SHANK


SHANK ONLY **DRILLED**

FOR DRILLED HEAD ADD "H" AND "A" **EXAMPLE:** AN6H-10A



HEAD ONLY DRILLED

FOR DRILLED HEAD AND SHANK ADD "H" ONLY EXAMPLE: **AN6H-10**



SHANK DRILLED

							(-) INDICATES CORROSION RESISTANT						
[Bolts are sold "EACH"		AN3					AN4					
,				Cadmium Plated AN3 (10-32)		Stainless AN3C (10-32)			Cadmium Plated AN4 (1/4-28)		Stainless AN4C (1/4-28)		
ĺ	Dash No.	Nominal Length	Grip Length	Drilled Price	Undrilled "A" Price	Drilled Price	Undrilled "A' Price	Grip Length	Drilled Price	Undrilled "A" Price	Drilled Price	Undrilled "A" Price	
	-3	15/32	1/16					1/16					
1 [-4	17/32	1/8				-	1/16					
4 [-5	21/32	1/4				-	3/16					
	-6	25/32	3/8					5/16					
	-7	29/32	1/2					7/16					
Į	-10	1-1/32	5/8					9/16					
	-11	1-5/32	3/4					11/16					
	-12	1-9/32	7/8					13/16					
	-13	1-13/32	1				-	15/16					
	-14	1-17/32	1-1/8				-	1-1/16					
	-15	1-21/32	1-1/4					1-3/16					
,	-16	1-25/32	1-3/8			-	-	1-5/16			-		
•	-17	1-29/32	1-1/2					1-7/16					
	-20	2-1/32	1-5/8					1-9/16					
	-21	2-5/32	1-3/4			-	-	1-11/16			-		
	-22	2-9/32	1-7/8			-		1-13/16			-		
	-23	2-13/32	2			-		1-15/16			-		
	-24	2-17/32	2-1/8			-		2-1/16			-		
Į	-25	2-21/32	2-1/4			-		2-3/16			-		
Į	-26	2-25/32	2-3/8			-		2-5/16			-		
	-27	2-29/32	2-1/2			-		2-7/16			-		
ļ	-30	3-1/32	2-5/8			-		2-9/16			-		
ļ	-31	3-5/32	2-3/4			-	-	2-11/16			-	-	
	-32	3-9/32	2-7/8			-	-	2-13/16			-	-	
1	-33	3-13/32	3			-	-	2-15/16			-	-	
ו	-34	3-17/32	3-1/8			-	-	3-1/16			-	-	
ļ	-35	3-21/32	3-1/4			-		3-3/16			-	-	
	-36	3-25/32	3-3/8			-	-	3-5/16			-	-	
ļ	-37	3-29/32	3-1/2			-	-	3-7/16			-	-	
ļ	-40	4-1/32	3-5/8			-	-	3-9/16			-	-	
	-41	4-5/32	3-3/4			-	-	3-11/16			-	-	
D	-42	4-9/32	3-7/8			-	-	3-13/16			-	-	
	-43	4-13/32	4	-		-	-	3-15/16			-	-	
_	-44	4-17/32	4-1/8			-	-	4-1/16			-	-	
	-45	4-21/32	4-1/4			-	-	4-3/16			-	-	
ļ	-46	4-25/32	4-3/8			-	-	4-5/16			-	-	
	-47	4-29/32	4-1/2			-	-	4-7/16			-	-	
	-50	5-1/32	4-5/8			-	-	4-9/16			-	-	
D.	-51	5-5/32	4-3/4			-	-	4-11/16			-	-	
Ų	-52	5-9/32	4-7/8	-		-	-	4-13/16			-	-	
	-53	5-13/32	5	-	-	-	-	4-15/16	-		-	-	
ļ	-54	5-17/32	5-1/8			-	-	5-1/16	-		-	-	
ļ	-55	5-21/32	5-1/4	-		-	-	5-3/16			-	-	
	-56	5-25/32	5-3/8			-	-	5-5/16			-	-	
	-57	5-29/32	5-1/2	-		-	-	5-7/16			-	-	
Į	-60	6-1/32	5-5/8			-	-	5-9/16			-	-	

Quantity discount on AN4 bolts - 15% discount on qty of 50-99 • 20% discount on qty of 100+