BOLTS



AN BOLT GAUGE Easy to use bolt gauge quickly and accurately identifies the diameters and lengths of "AN" bolts ranging from AN3-3 to AN10-50. There is also a handy reference guide on the back to help you identify the specific type of bolt from its head markings (symbology) and pre-drilled holes. 1 lbs (0.5Kg) shipping weight. Automatically sizes all AN bolts up to 5/8" diameter and 5 inches long.

P/N 04-05400

AN5 BOLTS AND AN6 BOLTS Hex head aircraft bolts are made of high-strength type 4037 or 8740 alloy steel (type 8740 is most commonly used). The bolts are centerless ground and threaded after heat treatment. Minimum tensile strength 125,000 PSI. Cadmium plated per specification QQ-P-416A, Type II, Class 3.

Bolts are sold "EACH" ALL BOLTS		AN5							AN6		
			Cadmium Plated AN5 (5/16-24)		Stainless AN5C (5/16-24)			Cadmium Plated AN6 (3/8-24)		Stainless AN6C (3/8-24)	
Dash No.	Nominal Length	Grip Length	Drilled Price	Undrilled "A" Price	Drilled Price	Undrilled "A" Price	Grip Length	Drilled Price	Undrilled "A" Price	Drilled Price	Undrilled "A" Price
-4	19/32	1/16					1/16			-	-
-5	23/32	3/16					1/16				
-6	27/32	5/16					3/16				
-7	31/32	7/16					5/16				
-10	1-3/32	9/16			-		7/16			-	
-11	1-7/32	11/16			-		9/16				
-12	1-11/32	13/16					11/16				
-13	1-15/32	15/16			-		13/16			· ·	
-14	1-19/32	1-1/16			-		15/16				
-15	1-23/32	1-3/16			-		1-1/16				
-16	1-27/32	1-5/16			-	-	1-3/16				
-17	1-31/32	1-7/16			-		1-5/16				
-20	2-3/32	1-9/16			-		1-7/16			· ·	
-21	2-7/32	1-11/16			-		1-9/16			-	-
-22	2-11/32	1-13/16			-	-	1-11/16			-	-
-23	2-15/32	1-15/16			-	-	1-13/16				-
-24	2-19/32	2-1/16			-	-	1-15/16			· -	-
-25	2-23/32	2-3/16			-		2-1/16			· ·	-
-26	2-27/32	2-5/16			-		2-3/16			· ·	-
-27	2-31/32	2-7/16			-		2-5/16			-	-
-30	3-3/32	2-9/16			-	-	2-7/16			· -	-
-31	3-7/32	2-11/16			-	-	2-9/16			-	-
-32	3-11/32	2-13/16			-	-	2-11/16			· ·	
-33	3-15/32	2-15/16			-	-	2-13/16			-	-
-34	3-19/32	3-1/16			-	-	2-15/16			-	-
-35	3-23/32	3-3/16			-	-	3-1/16				-
-36	3-27/32	3-5/16			-	-	3-3/16			-	-
-37	3-31/32	3-7/16			-	-	3-5/16			-	-
-40	4-3/32	3-9/16			-	-	3-7/16			-	-
-41	4-7/32	3-11/16			-	-	3-9/16			-	-
-42	4-11/32	3-13/16	-		-	-	3-11/16			-	-
-43	4-11/32	3-15/16			-	-	3-13/16			-	-
-44	4-19/32	4-1/16	-		-	-	3-15/16			-	-
-45	4-13/32	4-3/16			-	-	4-1/16			-	-
-46	4-27/32	4-5/16					4-3/16			-	-
-40	4-31/32	4-7/16			-	-	4-5/16			-	-
-50	5-3/32	4-9/16			-	-	4-7/16			-	-
-50	5-7/32	4-11/16			-	-	4-9/16			-	-
-52	5-11/32	4-13/16			-	-	4-11/16			-	-
-53	5-15/32	4-15/16			-	-	4-13/16			-	-
-53	5-19/32	5-1/16			-	-	4-13/16				-
-54	5-19/32	5-1/16			-	-	5-1/16			-	-
-55	5-23/32	5-5/16			-	-	5-3/16			-	-
-56	5-27/32	5-5/16					5-5/16				
	6-3/32	5-7/16			-	-				-	-
-60	0-3/32	0-9/10			-	-	5-7/16			-	-