

MACHINE SCREWS

MS27039 & MS27039C MACHINE SCREWS



Pan head low alloy steel machine screws have 125,000 to 145,000 psi tensile strength with cadmium plate finish to QQ-P-416, Type 2, Class 3. MS27039C screws are stainless steel Manufactured to MIL-S-6050 or MIL-8695. Equivalent to NAS 220.

| Part Number | Thread | Length (In.) | Grip Length (in) | MS27039 Price | MS27039C Price |
|--------------|--------|--------------|------------------|---------------|----------------|
| MS27039-0804 | 8-32 | 9/32 | --- | --- | --- |
| MS27039-0805 | 8-32 | 11/32 | --- | --- | --- |
| MS27039-0806 | 8-32 | 13/32 | --- | --- | --- |
| MS27039-0807 | 8-32 | 15/32 | --- | --- | --- |
| MS27039-0808 | 8-32 | 17/32 | .094 | --- | --- |
| MS27039-0809 | 8-32 | 19/32 | .156 | --- | --- |
| MS27039-0810 | 8-32 | 21/32 | .219 | --- | --- |
| MS27039-0811 | 8-32 | 23/32 | .281 | --- | --- |
| MS27039-0812 | 8-32 | 25/32 | .344 | --- | --- |
| MS27039-0813 | 8-32 | 27/32 | .406 | --- | --- |
| MS27039-0814 | 8-32 | 29/32 | .469 | --- | --- |
| MS27039-0815 | 8-32 | 31/32 | .531 | --- | --- |
| MS27039-0816 | 8-32 | 1-1/32 | .594 | --- | --- |
| MS27039-0817 | 8-32 | 1-3/32 | .656 | --- | --- |
| MS27039-0818 | 8-32 | 1-5/32 | .719 | --- | --- |
| MS27039-0819 | 8-32 | 1-7/32 | .781 | --- | --- |
| MS27039-0820 | 8-32 | 1-9/32 | .844 | --- | --- |
| MS27039-0821 | 8-32 | 1-11/32 | .906 | --- | --- |
| MS27039-0822 | 8-32 | 1-13/32 | .969 | --- | --- |
| MS27039-0823 | 8-32 | 1-15/32 | 1.031 | --- | --- |
| MS27039-0824 | 8-32 | 1-17/32 | 1.094 | --- | --- |
| MS27039-1-04 | 10-32 | 9/32 | --- | --- | --- |
| MS27039-1-05 | 10-32 | 11/32 | --- | --- | --- |
| MS27039-1-06 | 10-32 | 13/32 | --- | --- | --- |
| MS27039-1-07 | 10-32 | 15/32 | --- | --- | --- |
| MS27039-1-08 | 10-32 | 17/32 | .062 | --- | --- |
| MS27039-1-09 | 10-32 | 19/32 | .125 | --- | --- |
| MS27039-1-10 | 10-32 | 21/32 | .188 | --- | --- |
| MS27039-1-11 | 10-32 | 23/32 | .250 | --- | --- |
| MS27039-1-12 | 10-32 | 25/32 | .312 | --- | --- |
| MS27039-1-13 | 10-32 | 27/32 | .375 | --- | --- |
| MS27039-1-14 | 10-32 | 29/32 | .438 | --- | --- |
| MS27039-1-15 | 10-32 | 31/32 | .500 | --- | --- |
| MS27039-1-16 | 10-32 | 1-1/32 | .563 | --- | --- |
| MS27039-1-17 | 10-32 | 1-3/32 | .625 | --- | --- |
| MS27039-1-18 | 10-32 | 1-5/32 | .688 | --- | --- |
| MS27039-1-19 | 10-32 | 1-7/32 | .750 | --- | --- |
| MS27039-1-20 | 10-32 | 1-9/32 | .813 | --- | --- |
| MS27039-1-21 | 10-32 | 1-11/32 | .875 | --- | --- |
| MS27039-1-22 | 10-32 | 1-13/32 | .938 | --- | --- |
| MS27039-1-23 | 10-32 | 1-15/32 | 1.000 | --- | --- |

| Part Number | Thread | Length (In.) | Grip Length (in) | MS27039 Price | MS27039C Price |
|--------------|--------|--------------|------------------|---------------|----------------|
| MS27039-1-24 | 10-32 | 1-17/32 | 1.062 | --- | --- |
| MS27039-1-25 | 10-32 | 1-19/32 | 1.125 | --- | --- |
| MS27039-1-26 | 10-32 | 1-21/32 | 1.188 | --- | --- |
| MS27039-1-27 | 10-32 | 1-23/32 | 1.250 | --- | --- |
| MS27039-1-28 | 10-32 | 1-25/32 | 1.312 | --- | --- |
| MS27039-1-29 | 10-32 | 1-27/32 | 1.375 | --- | --- |
| MS27039-1-30 | 10-32 | 1-29/32 | 1.438 | --- | --- |
| MS27039-1-31 | 10-32 | 1-31/32 | 1.500 | --- | --- |
| MS27039-1-32 | 10-32 | 2-1/32 | 1.563 | --- | --- |
| MS27039-4-06 | 1/4-28 | 13/32 | --- | --- | --- |
| MS27039-4-07 | 1/4-28 | 15/32 | --- | --- | --- |
| MS27039-4-08 | 1/4-28 | 17/32 | --- | --- | --- |
| MS27039-4-09 | 1/4-28 | 19/32 | .062 | --- | --- |
| MS27039-4-10 | 1/4-28 | 21/32 | .125 | --- | --- |
| MS27039-4-11 | 1/4-28 | 23/32 | .188 | --- | --- |
| MS27039-4-12 | 1/4-28 | 25/32 | .250 | --- | --- |
| MS27039-4-13 | 1/4-28 | 27/32 | .312 | --- | --- |
| MS27039-4-14 | 1/4-28 | 29/32 | .375 | --- | --- |
| MS27039-4-15 | 1/4-28 | 31/32 | .438 | --- | --- |
| MS27039-4-16 | 1/4-28 | 1-1/32 | .500 | --- | --- |
| MS27039-4-17 | 1/4-28 | 1-3/32 | .563 | --- | --- |
| MS27039-4-18 | 1/4-28 | 1-5/32 | .625 | --- | --- |
| MS27039-4-19 | 1/4-28 | 1-7/32 | .688 | --- | --- |
| MS27039-4-20 | 1/4-28 | 1-9/32 | .750 | --- | --- |
| MS27039-4-21 | 1/4-28 | 1-11/32 | .813 | --- | --- |
| MS27039-4-22 | 1/4-28 | 1-13/32 | .875 | --- | --- |
| MS27039-4-23 | 1/4-28 | 1-15/32 | .938 | --- | --- |
| MS27039-4-24 | 1/4-28 | 1-17/32 | 1.000 | --- | --- |

HA

MS35190 MACHINE SCREWS (CROSS RECESSED)



82° flat head machine screws have 55,000psi minimum tensile strength and feature cadmium plate finish per QQ P-416, Type 2, Class 3. Manufactured from carbon steel to Federal Standard #66.

| Part Number | Old AN505R | Dia. - Thread Size | Length (In.) | Price |
|-------------|------------|--------------------|--------------|-------|
| MS35190-221 | -4R4 | 4-40 | 1/4 | --- |
| MS35190-222 | -4R5 | 4-40 | 5/16 | --- |
| MS35190-225 | -4R8 | 4-40 | 1/2 | --- |
| MS35190-226 | -4R10 | 4-40 | 5/8 | --- |
| MS35190-234 | -6R4 | 6-32 | 1/4 | --- |
| MS35190-236 | -6R6 | 6-32 | 3/8 | --- |
| MS35190-238 | -6R8 | 6-32 | 1/2 | --- |
| MS35190-239 | -6R10 | 6-32 | 5/8 | --- |
| MS35190-240 | -6R12 | 6-32 | 3/4 | --- |
| MS35190-250 | -8R5 | 8-32 | 5/16 | --- |
| MS35190-253 | -8R8 | 8-32 | 1/2 | --- |
| MS35190-254 | -8R10 | 8-32 | 5/8 | --- |