## ER HEAD SCREWS - DRIVE SCR VS



AN500, AN501 FILLISTER HEADSCREWS

AN500 (coarse thread) & AN501 (fine thread) slotted fillister head screws are fabricated from carbon steel. Tensile strength 60,000 PSI. Cadmium plated, Type II Class 3. If there is an "A" after the dash, the part is cadmium plated, Type II, Class 3, with a drilled head. If there isn't an "A" after the

dash, the part is Cadmium plated, Type I.

AN500							AN500AD STAINLESS STEEL					
AN500 Dash No.*	MS35265 Dash No.	Length (In.)	Thread Size	Price ea. Drilled	Price ea. Undrilled		AN500 Dash No.*	MS35275 Dash No.	Length (In.)	Thread Size	Pri D	
-A4-3	MS35265-12	3/16	4-40				-AD2-2	-201	1/8	2/56		
-A4-4	MS35265-13	1/4	4-40				-AD2-3	-202	3/16	2/56		
-A4-5	MS35265-14	5/16	4-40				-AD2-4	-203	1/4	2/56		
-A4-6	MS35265-15	3/8	4-40				-AD2-5	-204	5/16	2/56		
-A4-7	MS35265-16	7/16	4-40				-AD2-6	-205	3/8	2/56		
-A4-8	MS35265-17	1/2	4-40				-AD2-7	-206	7/16	2/56		
-A4-10	MS35265-18	5/8	4-40				-AD2-8	-207	1/2	2/56		
-A4-12	MS35265-19	3/4	4-40				-AD2-10	-208	5/8	2/56		
-A6-4	MS35265-26	1/4	6-32				-AD2-12	-209	3/4	2/56		
-A6-5	MS35265-27	5/16	6-32				-AD4-2	-211	1/8	4-40		
-A6-6	MS35265-28	3/8	6-32				-AD4-3	-212	3/16	4-40		
-A6-7	MS35265-29	7/16	6-32				-AD4-4	-213	1/4	4-40		
-A6-8	MS35265-30	1/2	6-32				-AD4-6	-215	3/8	4-40		
-A6-10	MS35265-31	5/8	6-32				-AD4-7	-216	7/16	4-40		
-A6-12	MS35265-32	3/4	6-32				-AD4-8	-217	1/2	4-40		
-A6-14	MS35265-33	7/8	6-32				-AD4-10	-218	5/8	4-40		
-A8-4	MS35265-41	1/4	8-32				-AD4-12	-219	3/4	4-40		
-A8-5	MS35265-42	5/16	8-32				-AD4-14	-220	7/8	4-40		
-A8-6	MS35265-43	3/8	8-32				-AD4-16	-221	1	4-40		
-A8-7	MS35265-44	7/16	8-32				-AD6-4	-226	1/4	6-32		
-A8-8	MS35265-45	1/2	8-32				-AD6-5	-227	5/16	6-32		
-A8-10	MS35265-46	5/8	8-32				-AD6-6	-228	3/8	6-32		
-A8-12	MS35265-47	3/4	8-32				-AD6-7	-229	7/16	6-32		
-A8-14	MS35265-48	7/8	8-32				-AD6-8	-230	1/2	6-32		
-A8-16	MS35265-49	1	8-32				-AD6-10	-231	5/8	6-32		
-A10-4	MS35265-59	1/4	10-24				-AD6-12	-232	3/4	6-32		
-A10-5	MS35265-60	5/16	10-24				-AD6-14	-233	7/8	6-32		
-A10-6	MS35265-61	3/8	10-24				-AD6-16	-234	1	6-32		
-A10-7	MS35265-62	7/16	10-24				-AD8-5	-242	5/16	8-32		
-A10-8	MS35265-63	1/2	10-24				-AD8-6	-243	3/8	8-32		
-A10-10	MS35265-64	5/8	10-24				-AD8-7	-244	7/16	8-32		
-A10-10	MS35265-65	3/4	10-24				-AD8-8	-245	1/2	8-32		
-A10-12	MS35265-66	1	10-24				-AD8-10	-246	5/8	8-32		
-A10-10	MS35265-79	1/2	1/4-20				-AD8-10	-240	3/4	8-32		
-A416-10	MS35265-80	5/8	1/4-20				-AD8-12 -AD8-14	-247	7/8	8-32		
-416-12	MS35265-81	3/4					-AD8-14	-240	1	8-32		
-410-12	101335205-61	AN501	1/4-20				-AD6-10		01AD STA		CCI	
AN501	MS35266	Length	Thread	Price ea.	Price ea.		AN501	MS35276	Length	Thread	Pri	
Dash No.*	Dash No.	(In.)	Size	Drilled	Undrilled		Dash No.*	Dash No.	(In.)	Size	D	
-8-12	-47	3/4	8-36				-AD10-5	-260	5/16	10-32		
-A10-4	-59	1/4	10-32				-AD10-6	-261	3/8	10-32		
-A10-6	-61	3/8	10-32				-AD10-7	-262	7/16	10-32		
-A10-8	-63	1/2	10-32				-AD10-8	-263	1/2	10-32	-	
-A10-10	-64	5/8	10-32									
-A10-12	-65	3/4	10-32				-AD10-10	-264	5/8	10-32	<u> </u>	
-A10-14	-66	7/8	10-32				-AD10-12	-265	3/4	10-32	<u> </u>	
-A10-16	-67	1	10-32				-AD10-14	-266	7/8	10-32		
-A10-20	-68	1-1/4	10-32				-AD10-16	-267	1	10-32		

Price ea.

Drilled

----

---

----

------

----

----

----

---

----

---

----

---

----

-------

----

---

---

---

----

----

----

---

----

---

---

----

--------

----

----

------

---

---

Price ea.

Drilled

----

----

----

---

---

----

----

----

Price ea.

Undrilled

---

---

------

---

---

---

---

---

---

\_\_\_\_

---

---

------

---

---

---

---

---

---

\_\_\_\_

----

---

---

------

---

---

----

----

---

---

---

---

Price ea.

Undrilled

---

----

----

---

---

---

---

---