

# LPS PRODUCTS



## LPS LOW SURFACE TENSION (LST)

A deep penetrating formulation attacks rust and corrosion to free "frozen" parts. LST has an extremely low surface tension that combines with a powerful foaming action to provide complete surface coverage, better penetration and improved moisture displacement. LST Penetrant lubricates and protects against rust and corrosion.  
11 oz. aerosol can.....P/N 09-01916

## LPS COPPER ANTI-SEIZE

Prevents seizure up to 1800°F (982°C). Lead free. Protects against seizure, heat-freeze, galling, rust and corrosion. Brushes easily. Highly adhesive on both wet and dry surfaces. Will not run, drip or settle out. Conforms to Mil-PRF-907E. Ideal for use on stainless steel and for joining dissimilar metals. Copper color 1/2 lb. can ...P/N 09-02908



## LPS MAGNUM TEFLON LUBRICANT

LPS® Magnum Teflon® Lubricant provides ultra-high lubricity, plus the additive strength of Teflon® for high-temperature, high-pressure environments. In even the most demanding situations, extend equipment life and reduce maintenance.  
11 oz. Spray Can.....P/N 09-26430

## LPS® HEAVY-DUTY SILICONE LUBRICANT

Meets FDA regulation for incidental food contact. Silicone-rich formula. Water-based formula. Colorless, odorless & non staining. Ideal for rubber and plastic surfaces. Eliminates sticking, binding and squeaking. Does not contain chlorinated solvents. Safe on most surfaces NSF® H1 registered. 13oz. (368g) – aerosol  
P/N 09-26410



## LPS FOOD GRADE SILICONE LUBRICANT

Food Grade Silicone Lubricant is a non-staining, high quality, lubricant designed especially for the food industry for use as an anti-stick agent for chutes and slides.  
10 oz.....P/N 09-04052

## LPS® COLDGALVANIZE CORROSION INHIBITOR

• Zinc purity greater than 99% • Works like a hot-dip on ferrous metals indoors and outdoors • Withstands water temperature up to 212°F (100°C) and continuous dry heat up to 750°F (400°C) • Commonly used as a flash rust preventive on welded areas • Long term protection • Flexible coating will not yellow, chalk, crack or peel • Electrochemically protects bare metal • Dries to touch in 3 to 5 minutes  
• 14oz. (397g) – aerosol.....P/N 09-26425



## LPS KB-88 ULTIMATE PENETRANT

KB 88 has extremely high solvency and special additives to enhance penetration and attack corrosion. It makes the toughest maintenance job easier, faster, safer, and simpler. Formulated to attack and quickly release rusted and corroded nuts, bolts, hinges, and other frozen components. High KB solvency value of 151 and low surface tension and penetrates faster and deeper than most other similar products in the market place. Displaces moisture with an aggressive formula that is NSF® Certified: H2 Registration # 138554 (Aerosol). This product is VOC compliant in all 50 states.  
13 oz.....P/N 09-04027  
20 oz.....P/N 09-04028



## LPS NICKEL ANTI-SEIZE

• Contains no lead, copper or graphite • Prevents seizure up to 2600°F (1427°C) • Protects against rust and corrosion • For use in hostile environments and • extreme temperatures • Acid resistant • Strong resistance to water washoff • Brushable to -18°F (-27°C)  
• Will not run, drip or settle out • Conforms to MIL-PRF-907E • Silver color.  
1/2 Lb .....P/N 09-04833  
1 Lb .....P/N 09-04834



## LPS T-91 NON-SOLVENT DEGREASER

T-91 Non-Solvent Degreaser is biodegradable, non-flammable, and has a neutral pH. T-91 is an excellent replacement for many solvent degreasers that have potential worker safety or flammability concerns. T-91 is ideal for solvent cleaning, part washers, and dip tanks and is more economical than most solvent degreasers in the marketplace. T-91 has an NSF® A1 registration (#141975) for use in food plants.  
Gallon .....P/N 09-02309  
Case of 4 Gallons .....P/N 09-02309-4



## LPS TRIFREE BRAKE CLEANER

The heavy-duty solvent for removal of brake fluid, grease, oil, and other contaminants.  
Single.....P/N 09-05843  
Case of 12 .....P/N 09-05843-12

## LPS INSTANT SUPER DEGREASER 2.0

An industrial strength degreaser with no brominated solvents, trichloroethylene or perchloroethylene for an improved health and safety profile.  
Case of 12 .....P/N 09-06057-12



## LPS® TKX® ALL-PURPOSE LUBRICANT

All purpose, value lubricant which displaces moisture, loosens rusted or frozen parts and protects metal against corrosion. Safe to use on most surfaces. High flash point of 175°F (79°C). Inverta Spray Valve allows user to spray in an upright or inverted position. NSF® H2 registration. 11oz. (312g) – aerosol .....P/N 09-00148

## LPS® HDX HEAVY-DUTY DEGREASER \*

• Nonflammable • Removes oil, grease, wax, dirt, moisture, tar, brake fluid and other contaminants • Fast evaporating • Low odor • Quick penetration • No residue • Non-conductive • NSF K1 registration # 059809: (aerosol); # 059810: (bulk)  
19oz. (539g) – aerosol .....P/N 09-26407



## LPS 1® PREMIUM LUBRICANT

Provides a dry, thin lubricating film. Resists oil, dust and dirt build-up. Fast acting penetration. Displaces moisture Loosens rusted or frozen parts. Provides a short term, light corrosion resistant barrier. Nonconductive Ideal for delicate mechanisms. Used worldwide in aviation. Safe on paint and most plastics.  
11oz. (312g) – aerosol .....P/N 09-25900  
1 gal. (3.78 l) .....P/N 09-26000

## LPS 2® HEAVY-DUTY LUBRICANT

Strong, multi-purpose lubricant and penetrant with added corrosion protection. Provides a nondrying, light, oily film for use on indoor/outdoor equipment. Reduces wear caused by friction and corrosion. Displaces moisture Loosens rusted or frozen parts. Provides up to one year of protection. Nonconductive Safe on paint and most plastics. Inverta Spray Valve allows user to spray in an upright or inverted position. NSF® H2 registered.  
11oz. (312g) – aerosol .....P/N 09-26100  
20 oz. Spray .....P/N 09-04752  
1 gal. (3.78 l) .....P/N 09-26200




## LPS 3® PREMIER RUST INHIBITOR

• Forms a transparent, soft, waxy film for protection & lubrication • Inhibits rust & corrosion, protects steel parts indoors for up to two years • Penetrates to displace moisture • Does not contain chlorinated solvents or silicone • Safe on most surfaces • Stops rust and corrosion • Provides non-sling lubrication • Provides anti-seize coating • Inverta Spray Valve allows user to spray in an upright or inverted position • NSF® H2 registered #129027: (aerosol); #059849 (bulk)  
11oz. (312g) – aerosol .....P/N 09-26300  
20fl. oz. (591ml) – trigger .....P/N 09-01223  
1 gal. (3.78 l) .....P/N 09-26400



## LPS® QB PRECISION DUSTER \*

Patented formula – Patented US #6,342,471. Electrical contact cleaner. Cleans electrical parts without harming plastics. • Non-flammable • Plastic safe • Non-conductive • No residue • Replaces HCFC 141b contact cleaners • Fast evaporating • Conforms to CARB VOC requirements.  
10 oz. spray can.....P/N 09-26210



## LPS 2® BELT DRESSING

LPS Belt Dressing is formulated to extend belt life, prevent belt slippage and resist water wash out. **Features:** • May be used in wet, outdoor conditions • Does not deteriorate drive belts • Eliminates squeaks from slipping belts • NSF® Certified: H1 Registration # 134508 8 Metal detectable plastic components-DETEX™ .....P/N 09-04434



## LPS CHAINMATE® CHAIN & WIRE ROPE LUBRICANT

ChainMate® Chain & Wire Rope Lubricant is moly-fortified and will perform under severe loads and extreme temperatures. Fortified with molybdenum disulfide, increases chain and wire rope life, effective under extreme pressure and temperature ranges. Contains water displacing solvents to quickly penetrate into cracks and core of wire rope.....P/N 09-04778



## LPS A-151 SOLVENT DEGREASER

LPS A-151 Solvent Degreaser 15oz.  
Single.....P/N 09-05423  
Case of 12 .....P/N 09-05423-12



## STRONG STEEL STICKS



Easy-to-use, hand-kneadable stick for immediate repairs to steel equipment and surfaces. Ideal for stopping leaks, even works on underwater applications. Permanently fills gaps and holes in metal, concrete, wood, fiberglass, and ceramics. Has a working time of 4 minutes, and will fully cure in 30 minutes to form a durable mass which can be machined, drilled, and painted. Can be used for many types of repairs, such as plumbing, electrical, ceramic, vehicle, equipment, and machinery. It is ideal for patching holes and cracks in pipes, drums, and tanks. 4 oz. stick.....P/N 09-26444

**\*ATTENTION: Volatile Organic Compounds (VOCs) Government Regulations: Product cannot be purchased, sold or used in the states listed below. CA, CT, DC, DE, IL, IN, ME, MD, MA, MI, NH, NJ, NY, OH, PA, RI, VA**

**NOTE: FOR CASE OF 12 CANS OF LPS PRODUCTS ADD -12 TO THE PART NUMBER.**