

LUBRICANTS - SEALANTS

LOCTITE THREADLOCKER

Loctite Threadlocker used on a standard fastener can eliminate expensive locking devices while you increase the reliability and quality of your assembly. One drop prevents loosening. 2 removable strengths for large & small applications and permanent strength for locking parts you never want to take apart.

#222 THREADLOCKER (permanent, for small screws)

10 ml.....P/N 09-42605
50 ml.....P/N 09-42610

#242 THREADLOCKER (removable, for large screws) (Blue)

.5 ml.....P/N 15-07264
10 ml.....P/N 09-42615..... 50 ml
P/N 09-42620

#262 THREADLOCKER (permanent, for large screws)

10 ml.....P/N 09-42625..... 50 ml
P/N 09-42630

#271 THREADLOCKER (permanent locking and sealing of threaded fasteners up to 1' (25 mm) in diameter) (Red)

10 ml.....P/N 09-04687

LOCTITE 515 GASKET ELIMINATOR

Henkel Loctite 515 Gasket Eliminator is a high viscosity, flexible sealant for use on rigid machined flanges. It provides resistance to low pressures immediately after assembly of flanges. 50 ml Tube.....P/N 09-04568

LOCTITE® 609™ RETAINING COMPOUND

LOCTITE® 609™ Retaining Compound General Purpose is a low viscosity, rapid-curing anaerobic adhesive that augments the strength of press fit assemblies or slip fit assemblies up to 0.006" in diameter. Adds up to 3,000 psi holding power. Recommended for parts that will need subsequent dismantling, i.e., retention of bearings onto shafts and into housings. Mil Spec (R-46082B) Type I.

50 ml.....P/N 09-04652

NIEL SEAL GASKET AND JOINT SEALING COMPOUND

N20-66 Seals threaded pipe joints, machined surfaces and flare nuts. Used on engine rear sections, sump gaskets, triple connector threads, channel plugs, air control valves, dump valve guides, water separator glasses, and for all metal-to-metal unions with any kind of gasket. A special paste-type density for threaded pipe joints, gasoline and carburetor connections, water heater fittings, gas range valves, etc.

1 Lb. Can Light Weight.....P/N 04-03925
5 Lb. Can Light Weight.....P/N 04-03971
1 Lb. Can Medium Weight.....P/N 04-03972
5 Lb. Can Medium Weight.....P/N 04-03973

PARKER-O-LUBE

This Lubricant is excellent for use on exposed valve plungers, cylinder rods, and other o-rings. It lubricates without causing deterioration of rubber and is water resistant. Good for low pressure vacuum and pneumatic systems.

2 oz. Tube P/N 05-13059

LUBRIPLATE NO. 630AA

Multi-purpose lubricant. Forms a wearing film on working surfaces. Excellent protection against rust and corrosion. Recommended for controllable pitch props, wheel and mag-neto bearings, general greasing.

16 oz. Tub.....P/N 09-25400
6 Lb. ContainerP/N 09-25500

12/34 MIRACLE FORMULA LUBRICANT

Meets MIL Spec MIL-C-23411. 12/34 MIRACLE FORMULA® has the most effective ALL-IN-ONE formulation on the market today. Its lubricating, moisture displacing, penetrating and corrosion prevention is unsurpassed in any single product type of its kind. Don't accept substitutes, ask for 12/34 MIRACLE FORMULA® by name.

Lubricates: Contains highly refined lubricants which provide superior protection and anti-wear properties. **Removes Moisture:** Moisture is lifted and displaced rather than trapped. Pores and crevices of surface are freed from moisture and are coated with a thin non-greasy film that prevents additional moisture from clinging or reentering. **Penetrates:** Rusted and frozen metal parts - nuts, bolts, studs, pins, etc. - are easily loosened by means of superior "creepability". **Prevents Rust & Corrosion:** Thin film adheres to metallic surfaces, providing positive temporary protection against the formation of rust and corrosion, including electrolysis and galvanic corrosion common in salt environments.

11 oz. aerosol.....P/N 09-04443

STRIKE-HOLD CLEANER, LUBRICANT, PROTECTANT

Strikehold® is a fast-acting, penetrating compound that cuts through dirt, rust and corrosion, quickly getting into metal parts that have become frozen or encrusted. Strikehold® provides a long-lasting dry lubricant, which reduces friction. It helps dry out wet electrical gears and other water sensitive parts, and will actually improve electrical performance by cleaning and protecting contacts and internal parts, including circuitry and connections. Strikehold® protects by providing a shield-like film against the effects of moisture and corrosion, even against salt water, while repelling sand, dirt and dust.

12 oz Aerosol.....P/N 09-06169
16 oz TriggerP/N 09-06170
5 L Jug.....P/N 09-06171

FOAMING SUPERIOR LUBRICANT

Tri-Flow is revolutionizing the way you clean, protect and lubricate all of your moving parts with the introduction of Foaming Superior Lubricant and Foaming Citrus Cleaner Degreaser. Tri-Flow's powerful foaming action clings to both horizontal and vertical surfaces to allow for deep penetration and accurate application. Tri-Flow Foaming products are ideal for use on bicycles, firearms, sporting equipment, manufacturing equipment, and more!.....P/N 09-02082

EZ TURN LUBRICANT (FUELUBE)

EZ Turn is a specialty lubricant/sealant used for fuel and oil line valves and is resistant to high temperatures. It is especially effective where high octane fuels and aromatics are present. EZ Turn is also extremely efficient as a gasket paste and anti-seize agent. EZ Turn will not gum, crack or dry out. Each shipment is independently tested. Excellent for tapered plug valves, aircraft engine manufacturing, and marine applications. EZ Turn is the functional equivalent of fuel lube.

5 oz. tube.....P/N 09-00306
1 Lb. can.....P/N 09-00180

DYKEM CROSS-CHECK TORQUE SEAL

DYKEM® Cross-Check™ provides a convenient visual method for identification of vibratory loosening or tampering in nuts, bolts, fasteners, and assemblies. Provides warranty protection against tampering. Marks will be easily broken if parts are tampered with or become loose. Highly visible under ambient light. Excellent adhesion to metal and other substrates. **Features:** • It's like a wax seal for critical holds and fastening • Tamper-Proof Torque Mark • Safe for most surfaces • Highly visible • Excellent adhesion • Visually detects loose nuts & bolts • Provides warranty protection • Dries to the touch: 1-2 hours • Fully cured: 24 hours • GHS compliant labeling • Two year shelf life • Boeing Specification: BMS8-45 Type II.

Description	Color	Size	Part No.	Price
Cross Check Torque Seal	Red	1 oz	09-02033-1	---
Cross Check Torque Seal	Yellow	1 oz	09-25807-1	---
Cross Check Torque Seal	Green	1 oz	09-25808-1	---
Cross Check Torque Seal	Blue	1 oz	09-25809-1	---
Cross Check Torque Seal	Orange	1 oz	09-25810-1	---
Cross Check Torque Seal	Gray	1 oz	09-04690-1	---
Cross Check Torque Seal	White	1 oz	09-02411-1	---
Cross Check Torque Seal	Pink	1 oz	09-04444-1	---

NOTE: FOR CASE OF 24 (1 OUNCE) TUBES ADD -24 TO THE PART NUMBER.

DYKEM® CROSS-CHECK™ PLUS AVIATION GRADE TORQUE SEAL - SKYDROL® RESISTANT

DYKEM® Cross Check Plus Skydrol®-Resistant Torque Seal® has been certified to meet the Boeing specification BMS8-45H Type I/III for a Skydrol-resistant, quick-dry tamper proof marker. This specification requires strict adherence to key performance properties such as dry-to-touch time, full cure time, Skydrol resistance, and dielectric strength, along with other critical physical, mechanical, and flammability requirements.

Description	Color	Size	Part No.	Price
Cross Check Plus Skydrol Resistant Tamper Evident Lacquer	Blue	1 oz	09-05509	---
Cross Check Plus Skydrol Resistant Tamper Evident Lacquer	Yellow	1 oz	09-25811-1	---
Cross Check Plus Skydrol Resistant Tamper Evident Lacquer	Pink	1 oz	09-03486-1	---