TRON INSTRUM

MILITARY CHRONOMETER



- Military clock Two button control system · Control switch has remote capability · Sunlight
- readable displays N.V.G. Filter, Green A or BG7B Manual dimming of the display Full 6 digit display selectable, GMT, LT, ET • Elasped time is count up or down • Keep alive battery (2 year life) • GMT full 6 digit hours/minutes/seconds • Local Time, 24 hour, 4 digit

Description	Part No.	Price
GMT, LT & ET Clock with night vision compatibility for military (BG7B)		
GMT, LT & ET Clock with night vision compatibility for military (Green A)	11-08022	-



DENSITY & PRESSURE ALTITUDE MODEL 655

 OAT (F) & OAT (C) Pressure & Density Altitude With Pressure ALT. Alarm Aircraft Voltage with Flashing Alarm • Bright Sunlight Readable Displays • Input Voltage 11 TO 28 Volts • Complete with 12 FT. Digital Probe

Description	Part No.	Price
Front Mount	10-24515-1	
Rear Mount	10-24515-2	



Rear Mount

DIGITAL VOLTMETER OUTSIDE

AIR TEMPERATURE MODEL 303

OAT (F) & OAT (C) • Aircraft Voltage with Flashing Alarm • Bright Sunlight Readable Displays • Input Voltage 11 TO 28 Volts • Complete with 12 FT. Digital

Description	Part No.	Price
Front Mount	10-24565-14-1	
Rear Mount	10-24565-14-2	



DIGITAL VOLTMETER AMMETER MODEL 475VA/475VAA





- Low current drain .001 amp
- Plus 100.0 volt D.C. range
- 1.3" case depth
- · Sunlight readable
- One tenth volt resolution
- Plus or minus 100.0 amp range
- 21/4 Standard mount
- 5, 14, or 28 volt back lighting
- · One tenth amp resolution

The M475VAA has dual shunts and can read voltage and two current flows (M475VA has a single shunt). The 475VA and the 475VAA were designed for low current drain and are also used in standby and emergency battery packs. One example of safety is if the alternator fails, you can monitor the load current out of the battery.

Description	Part No.	Price
Volt/Amm Meter 14V Lighting (Single Shunt)	10-03319	
Volt/Amm Meter 28V Lighting (Single Shunt)	10-03320	
Volt/Amm Meter 14V Lighting (Double Shunt)	10-03321	
Volt/Amm Meter 28V Lighting (Double Shunt)	10-03322	
Volt/Amm Meter 14V Lighting (Single Shunt) With Night Vision Compatibility Green A	10-04562	
Volt/Amm Meter 28V Lighting (Single Shunt) With Night Vision Compatibility Green A	10-04564	
Volt/Amm Meter 14V Lighting (Double Shunt) With Night Vision Compatibility Green A	10-04566	
Volt/Amm Meter 28V Lighting (Double Shunt) With Night Vision Compatibility Green A	10-04567	



DAVTRON 307CD-PROBE MINI 2FT TEMPERATURE PROBE Davtron 307CD-Probe Mini 2ft Temperature Probe (Analog) 307CD, 307FD......P/N 10-07464



DAVTRON 9 PIN FEMALE CONNECTOR ASSEMBLY

Davtron Nut for Temp Probe.....P/N 10-07466



Please view our website for current prices.

DAVTRON NUT FOR TEMP PROBE

Davtron Nut for Temp Probe.....P/N 10-07465

DIGITAL OUTSIDE AIR TEMPERATURE

MODEL 301



- OAT (F)
- OAT (C)
- Bright Sunlight Readable Displays
- Input Voltage 11 TO 28 Volts.
- Complete with 12 FT. Digital Probe.

Description	Color	Part No.	Price
O.A.T. Celsius (301 C),	Amber LED	10-08312	
301C 3 Pin Connector for Probe	Amber LED	10-03316	
O.A.T. Fahrenheit (301 F)	Amber LED	10-08512	
301F 3 Pin Connector for Probe	Amber LED	10-03317	
O.A.T. Celsius,	Green LED	10-04543	
O.A.T. Celsius,	White LED	10-04544	
301C 3 Pin Connector For Probe	Green LED	10-04545	
301C 3 Pin Connector For Probe	White LED	10-04546	
O.A.T. Fahrenheit	Green LED	10-04547	
O.A.T. Fahrenheit	White LED	10-04548	
301F 3 Pin Connector For Probe	Green LED	10-04549	
301F 3 Pin Connector For Probe	White LED	10-04551	







M307FC

M307FCI

M307FCE

- OAT (F) & OAT (C) Voltage
- Input Voltage 11 TO 28 Volts.
- Bright Sunlight Readable Displays Complete with 12 FT. Digital Probe.

Description	Part No.	Price
O.A.T. F & C (307FC)	10-08513	
O.A.T. F & C Cabin Air (307FCI)	11-05881	
O.A.T. F & C & Voltmeter (307FCE)	10-04552	





Description	Part No.	Price
Celsius Differential Intercooler (307 CD)	10-03318	
Fahrenheit Differential Intercooler (307 FD)	11-05882	





MODEL 450

MODEL 451

- Aircraft Voltage with Flashing Alarm Aircraft Voltage (451)
- Bright Sunlight Readable Display Bright Sunlight Readable Display
- Input Voltage 11 TO 28 Volts. • Minimum panel Space
 - Input Voltage 11 TO 28 Volts.

Description	Part No.	Price
Voltmeter (450), Amber LED	10-24505	
Voltmeter (450), Amber LED, Remote Sensing	10-04555	
Voltmeter (450), Green LED	10-04553	
Voltmeter (450), Green LED, Remote Sensing	10-04556	
Voltmeter (450), White LED	10-04554	
Voltmeter (450), White LED, Remote Sensing	10-04557	
Voltmeter (451), Red LED, Remote Sensing	10-04558	

ACCESSORIES / REPLACEMENT PARTS

Description	Part No.	Price
KW-105G Display for Model 303, 307, 655, 880, & 903	11-04611	
KW-115G Display for Model 303, 655, 850, 877, & 880	11-04612	
KW-505F Digital Display for model 811B	11-04613	
800 Series Alarm Son-Alert	11-04610	
Temp Probe - 7Ft Red/Black Twisted (Analog)	10-00653	
Temp Probe - 12Ft COAX C307PS (Analog)	11-04603	
Temp Probe for 307CD/307FD (Analog)	11-04602	
Temp Probe 12Ft COAX D307PS (Digital)	11-10717	

See our website for additional sizes.