# ID CONTINENT CDIS – GPS – ANNUNCIATOR



#### MID-CONTINENT 2 INCH CDI

This indicator will fit the need of aircraft owners of LSA all the way up to business aircraft. The CDI allows for precise and accurate readings. Nav, GPS and VLOC annunciation are built-in and backlit by LED lighting, providing enhanced nighttime and sunlight readability. The CDI has TSO approval from the FAA and will interface with most nav and GPS receivers.

Specifications: • Power Input: Accepts 11 to 32 Volts DC. • Lighting: Internal white LED. Lighting control voltage is

selectable for 5, 14, or 28
Weight: 0.6 lbs. • Length: 3.5 inches

Mid-Continent Instruments and Avionics - CDI MD222-406

(This unit has the NAV/GPS & VLOC annunciations for the Garmin units) MD222-406 CDI GS Indicator ......P/N 11-05106 MD200-706 CDI GS Indicator ......P/N 10-06014

## MID-CONTINENT GPS ANNUNCIATORS With fingertip annunciation and flight



information in the pilot's primary view, Annunciation Control Units (ACU) offer important features in an efficient design. As an interface with popular NAV and GPS systems, the ACU provides vital

safety information including waypoint, approach status and integrity alerting. Approved to strict TSO standards, Mid-Continent Instru-ments and Avionics ACUs are engineered as a compact, affordable solution to the challenge of installing several switches. Most versions are configured 14V or 28V with vertical or horizontal mounting and feature long-life lamps with automatic photocell dimming.

GARMIN WAAS ACU - GNC 420W, GNS 430W/530W			
Model No.	Configuration	Part No.	Price
MD41-1510	28V Horz. for Garmin GTN650/750	10-04768	
MD41-1512	14V Horz. for Garmin GTN650/750	10-04769	
MD41-1464A	Horizontal, 14V (head only)	10-02665	
MD41-1468A	Horizontal, 28V (head only)	10-02663	
MD41-1484W	Horizontal, 14V WAAS	10-02657	
MD41-1488W	Horizontal, 28V WAAS	10-02659	
MD41-1498W	Vertical, 28V WAAS	10-02661	
GPS 400/500, GNC 420/520, GNS 430/530			

10-02672 MD41-1418A Vertical, 28V (head only)

#### **MID-CONTINENT GPS ANNUNCIATORS -**GARMIN WAAS ACU GTN 650 / 750 SERIES With fingertip annunciation and flight infor-

MSG mation in the pilot's primary view, annun-SUSP SUSP CDI

ciation control units (ACUs) offer important features in an efficient design. As an interface with popular NAV and GPS systems, the ACU provides vital safety

information, including waypoint, approach status and integrity alerting.

Model No.	Description	Part No.	Price
MD41-1512	Horizontal, 14V, LED lighting	10-04769	
MD41-1510	Horizontal, 28V, LED lighting	10-04768	
MD41-1514	Horizontal, 28V, 5V lighting, LED lighting	10-06768	
MD41-1511	Vertical, 28V, LED lighting	10-06770	
MD41-1515	Vertical, 28V, 5V lighting, LED lighting	10-06771	

#### **REMOTE SWITCHING RELAY UNITS**



730

Remote mounted 24-pole unit features eight Nitrogenfilled relays (3 poles per relay) with Gold-plated con-tacts. Ideal for GPS/VOR transfer and audio switching applications. Relays are activated individually by voltage or ground keying or as a group by ground keying. Versatile Mounting - Horizontal, Vertical or flat mount configurations. Fail-safe fault monitoring through inter-

locking of all internal relays. Adjustable dimmer output for external annunciations. Quality MIL-SPEC connector kit included. Specifications: Width: 2.86", Height: 1.52", Depth: 2.6", Weight: .75lbs Remote Relay Unit 14V TSO .....P/N 10-06793 Remote Relay Unit 28V TSO ......P/N 10-06016

#### MID-CONTINENT 3" CDI



The MD200 Series sets the standard for navigation instruments that are significantly more reliable, longer lasting and easier to read. Thousands have been sold by Garmin with the popular GNS 430/530 systems and the GTN Series touch-screen navigators. The MD200 Series is the preferred replacement for the Collins Micro Line IND 350 Series and replaces the BendixKing KI206. Built-in annunciators are easy to view and save hundreds of dollars on most installations.

These CDIs feature new-generation rectilinear meter movements for more accurate readings, plus a course selector and resolver output. The MD200 Series can be configured for 14V or 28V installations.

Features: • Fits standard 3 1/8" panel cutout • All-metal construction with stainless steel ball bearings in critical areas . Deviation bars/pointers hide from view when invalid • LED annunciations for NAV, GPS, VLOC and To/From indication • True OBS course resolver out • Compatible with WAAS GPS receivers Specifications: • Voltage Input: 12 - 32 VDC • Current Input: 0.2 amps max • Lighting: 5V, 14V, or 28V automatic photocell dimming of annunicators • Cutout: Standard 3 1/8" round

Model #	Description		Part No.	Price
MD200-706		14V Light Tray		
MD200-706		24V Light Tray	10-06014	
MD200-707	3-inch, L/R, Glideslope with annunciators, Course datum	5V, 14V, or 28V	10-06043	

### **MID-CONTINENT GPS ANNUNCIATORS -**HONEYWELL KGP 560/860



With fingertip annunciation and flight information in the pilot's primary view, annunciation control units (ACUs) offer important features in an efficient design. As an interface with popular NAV and

GPS systems, the ACU provides vital safety information, including waypoint, approach status and integrity alerting. 2-button, Horizontal, 28V MD41-1208......P/N 10-06788

#### MID-CONTINENT AVIONICS ANNUNCIATION CONTROL UNIT HORIZONTAL FOR GPS 155XL/GNC 300XL



With fingertip annunciation and flight information in the pilot's primary view, annunciation control units (ACUs) offer important features in an efficient design. As an interface with popular NAV and

GPS systems, the ACU provides vital safety information, including 

### **MID-CONTINENT GPS ANNUNCIATORS -GARMIN WAAS GNC 420W GPS** 400W / 500W- HORIZONTAL



With fingertip annunciation and flight information in the pilot's primary view, annunciation control units (ACUs) offer important features in an efficient design.

As an interface with popular NAV and GPS systems, the ACU provides vital safety information, including waypoint, approach status and integrity alerting. Horizontal, 28V (head only) MD41-1408A ..... P/N 10-02668

#### MID-CONTINENT AVIONICS ANNUNCIATION **CONTROL UNITS FOR GARMIN TAWS**



Designed to place annunciation and mode selection for the Terrain Awareness Warning System (TAWS) within the pilot's direct field of view, these annunciators

provide tactile feedback to the pilot through internally lighted push buttons. Featuring automatic photocell dimming and manual and remote test capability, units have excellent daylight readability.

Model No.	Description	Part No.	Price
MD41-1028	1-button, Horizontal, 28V, LED lighting	10-06782	
MD41-1048	3-button, HTAWS, Horizontal	10-06785	
MD41- 1048(5V)	3-button, HTAWS, Horizontal, 28V, LED lighting	10-06786	