# ERRY PULLING HEADS

#### **CHERRY PULLING HEAD H1900-456**

The H1900-456 is designed to reliably install all sizes of the single action NAS1919/1921 product assembled with or without a drive washer. To install the product without a drive washer use the appropriate nose piece. Total weight without riveter: .27 lbs (0.1222 kg). Use with G83 or G84 Cherry Riveter or any riveter equipped with a 352 Style Mounting .....P/N 12-03019 System.

# COMPACT UNIVERSAL STRAIGHT **PULLING HEAD H800**

Compact Universal Straight Pulling Head for G800 riveter. Weight - 0.15 lbs......P/N 12-03092

#### SHORT PINTAIL BASIC PULLING HEAD H513

Cherry Short Pintail Basic Pulling Head H513 -See Tool Specifications below to determine which nulling head is needed.

Panning restaura						
Cherry P/N	LockBolt Dia.	Installed Length	Part No.	Price		
H513-04-20	1/8"	2" (51 mm)	12-03020			
H513-04-35	1/8"	3-1/2" (89 mm)	12-03021			
H513-05-35	5/32"	3-1/2" (89 mm)	12-03022			
H513-06-20	3/16"	2" (51 mm)	12-03023			
H513-06-60	3/16"	6" (152 mm)	12-03024			
H513-08-35	1/4"	3-1/2" (89 mm)	12-03025			

#### SWIVEL NOSE PULLING HEAD H513S

Cherry Swivel Nose Pulling Head H513S - See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	LockBolt Dia.	Installed Length	Part No.	Price
H513S-05-20	2" (51 mm)	5/32"	12-03026	
H513S-05-35	3-1/2" (89 mm)	5/32"	12-03027	
H513S-06-20	2" (51 mm)	3/16"	12-03028	
H513S-06-24	2-3/8" (60 mm)	3/16"	12-03029	
H513S-06-35	3-1/2" (89 mm)	3/16"	12-03030	
H513S-06-48	4-13/16" (122 mm)	3/16"	12-03031	
H513S-08-24	2-3/8" (60 mm)	1/4"	12-03032	
H513S-08-35	3-1/2" (89 mm)	1/4"	12-03033	
H513S-08-48	4-13/16" (122 mm)	1/4"	12-03034	
H513S-10-27	2-11/16" (68 mm)	5/16"	12-03035	
H513S-10-42	4-3/16" (106 mm)	5/16"	12-03036	
H513S-12-27	2-11/16" (68 mm)	3/8"	12-03037	
H513S-12-42	4-3/16" (106 mm)	3/8"	12-03038	

# SELF RELEASING SWIVEL NOSE **PULLING HEAD H513SR**

Cherry Self Releasing Swivel Nose Pulling Head H513SR - See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	LockBolt Dia.	Installed Length	Part No.	Price
H513SR-05-20	2" (51 mm)	5/32"	12-03039	
H513SR-05-35	3-1/2" (89 mm)	5/32"	12-03040	
H513SR-06-20	2" (51 mm)	3/16"	12-03044	
H513SR-06-24	2-3/8" (60 mm)	3/16"	12-03045	
H513SR-06-35	3-1/2" (89 mm)	3/16"	12-03046	
H513SR-06-48	4-13/16" (122 mm)	3/16"	12-03047	
H513SR-08-24	2-3/8" (60 mm)	1/4"	12-03048	
H513SR-08-48	4-13/16" (122 mm)	1/4"	12-03049	
H513SR-10-27	2-11/16" (68 mm)	5/16"	12-03050	
H513SR-10-42	4-3/16" (106 mm)	5/16"	12-03051	
H513SR-12-27	2-11/16" (68 mm)	3/8"	12-03052	
H513SR-12-42	4-3/16" (106 mm)	3/8"	12-03053	

#### SELF RELEASING SWIVEL NOSE/ CHISEL SHAPE PULLING HEAD H513SRC

Cherry Self Releasing Swivel Nose/Chisel Shape Pulling Head H513SRC - See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	LockBolt Dia.	Installed Length	Part No.	Price
H513SRC-05-20	2" (51 mm)	5/32"	12-03054	
H513SRC-05-35	3-1/2" (89 mm)	5/32"	12-03055	
H513SRC-06-20	2" (51 mm)	3/16"	12-03056	
H513SRC-06-35	3-1/2" (89 mm)	3/16"	12-03057	
H513SRC-08-48	4-13/16" (122 mm)	1/4"	12-03058	

#### **CHERRYLOCK "A" CODE PULLING HEAD H84-8CLA**

Cherrylock "A" Code Pulling Head for use with G84 riveters. Tool weight (without riveter): .3 lbs (0.14 kg). .....P/N 12-03104



#### OFFSET LOCKBOLT/ SHORT PINTAIL PULLING HEAD H563SP

See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	Туре	LockBolt Dia.	Part No.	Price
H563SP-4B	Basic Pulling/Short Pintail	1/8"	12-03064	
H563SP-5B	Basic Pulling/Short Pintail	5/32"	12-03065	
H563SP-6B	Basic Pulling/Short Pintail	3/16"	12-03066	

#### CHERRYLOCK® STRAIGHT **PULLING HEAD H681**



Fits directly on all Cherry hydroshift riveters, 2-9/16" installed. Separate pulling head is required for each style & diameter rivet.

Description		A/B Dims.		
H681-3C Universal C-Sunk Head	3/32"	.163"/.332"	12-03070	
H681-4C Universal C-Sunk Head	1/8"	.208"/.341"	12-03071	
H681-4F Countersunk Head 156	1/8"	.430"/.358"	12-03072	
H681-4S Countersunk Head NAS 1097	1/8"	.174"/.341"	12-03073	
H681-5C Universal C-Sunk Head	5/32"	.269"/.352"	12-03074	
H681-6C Universal C-Sunk Head	3/16"	.335"/.386"	12-03075	
H681-6F Countersunk Head 156	3/16"	.625"/.367"	12-03076	
H681-6S Countersunk Head NAS 1097	3/16"	.281"/.386"	12-03077	
H681-8C Universal C-Sunk Head	1/4"	.458"/.398"	12-03078	

# CHERRYLOCK® STRAIGHT **PULLING HEAD H681B**



Fits directly on all Cherry hydroshift riveters, 2-9/16" installed. Separate pulling head is required for each style & diameter rivet.

Description	Rivet Dia.	A/B Dims.	Part No.	Price
H681B166-4 Uni-Sink Head	1/8"	.250" / .359"	12-03079	
H681B166-5 Uni-Sink Head	5/32"	.313" / .377"	12-03080	
H681B166-6 Uni-Sink Head	3/16"	.375" / .419"	12-03081	

# **CHERRYMAX® STRAIGHT** PULLING HEAD H701B-456



CherryMAX Straight Pulling Head H701B-456 - Installs 1/8", 5/32" & 3/16" Nominal & Oversize CherryMAX Rivets.

P/N 12-03083

#### **NUT PLATE PULLING HEAD WITH** NOSEPIECES H702-3NPR



Cherry® Nut Plate Pulling Head. Includes nose-pieces: 728A9-3 (3/32"") & 728A9-104 (1/8""). For G702A Riveter. Installs 3/32" & 1/8, 2.5 mm & 3 mm Nut Plate.

P/N 12-03084

#### CHERRYMAX STRAIGHT PULLING **HEAD H744A-8**



CherryMAX Straight Pulling Head installs 1/4" Nominal & Oversize CherryMAX Rivets (G744 Only) ......P/N 12-03087

# CHERRYMAX RIGHT ANGLE **PULLING HEAD H753A-456**

CherryMAX Right Angle Pulling Head H753A-456 installs 1/8", 5/32" & 3/16" Nominal & Oversize CherryMAX Rivets P/N 12-03089

# CHERRYMAX OFFSET PULLING HEAD H781-456



CherryMAX Offset Pulling Head installs 1/8", 5/32" & 3/16" Nominal & Oversize CherryMAX Rivets ......P/N 12-03090

#### OFFSET LOCKBOLT PULLING HEAD H563

See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	Type	LockBolt Dia.	Part No.	Price
H563-4B	Basic Pulling	1/8"	12-03061	
H563-5B	Basic Pulling	5/32"	12-03062	
H563-6B	Basic Pulling	3/16"	12-03063	

# **STRAIGHT PULLING HEAD -8** CHERRYMAX® H84A-8

Straight pulling head H84A-8 for use with G84 Power Riveter and G84-LS Split Power Riveter (with adaptor 744-700). Pulling Head Weight: 0.2 lbs (0.09 kg)......P/N 12-03106