# **STEELMAX POWER TOOLS - TENSIOMETERS**

### STEELMAX METAL CUTTING SAW 9 INCH



0 0 7				
Accessories	Teeth	Arbor	Part No.	Price
9" Stainless Steel Blade	80T	1.0"	12-01805	
9" Alluminum Blade	80T	1.0"	12-01807	

#### STEELMAX DRYCUT SAW S14 Utilizing a 14" carbide tipped blade, the Steelmax S14 cuts



through metal faster, safer and cleaner than abrasive chop saws in a fraction of the time and cost. Powered with a 15 amp motor and geared to turn slower than a chop saw, the S14 dry cutter cuts like a cold saw, but at a fraction of the cost. Sold standard with a 14" carbide tipped mild

steel blade attached, heavy duty, industrial strength cast iron base and two position locking vise, this saw is ready for immediate action! Cuts solid mild steel up to 1"thickness; cut profiles: pipe, angles, channel with a depth of cut up to 4-3/4". Bevels to 45 degrees. Saves time and money giving cool cuts that need little to no finishing, eliminating any need for grinding or cool down time.......P/N 12-01717

Accessories	Teeth	Arbor	Part No.	Price
14" Stainless Steel (Less Than 1/4")	90T	1.0"	12-01809	
14" Thin Mild Steel (Less Than 1/4")	90T	1.0"	12-01810	



# MAGNETIC BASE DRILL

# **CUTTERS FOR MAGNETIC BASE BRILL**

Dia.	D.O.C.	Part No.	Price	Dia.	D.C	).C.	Part N	o.	Price
7/16"	1"	12-01813		1/2"	2	?"	12-018	34	
1/2"	1"	12-01814		9/16"	2	2"	12-018	35	
9/16"	1"	12-01815		5/8"	2	2"	12-018	36	
5/8"	1"	12-01816		11/16"	2	"	12-018	37	
11/16"	1"	12-01817		3/4"	2	?"	12-018	38	
3/4"	1"	12-01818		13/16"	2	?"	12-018	39	
13/16"	1"	12-01819		7/8"	2	2"	12-018	40	
7/9"	1"	12-01829		15/16"	2	2"	12-018	41	
1"	1"	12-01831		1"	2"		12-018	42	
1-1/16"	1"	12-01832		1-1/16"	2	?"	12-018	43	
7/16"	1"	12-01833							
Accessories for Base Drill				Pa	rt No.		Price		
1" Center Pin For SM4374				12-	-01845				
1" Center For1" DOC Cutters			12-	-01844					
2" Center Pin For SM437L Only				12	-01847				
2" Center For 2" DOC Cutters				12-	-01846				

# **1/2 INCH CHUCK & ADAPTER**

With this optional industrial arbors and 2MT-1/2"Drill Chuck now you can! SteelMax industrial arbors let you easily adapt our premium m2AL cutters to a variety of machinery, including CNC, lathe's, stationary drill presses and similar equipment. With our integrated coolant collar, cutter performance and cutter life is assured!......P/N 12-01812

#### 6 AND 13 PIECE CUTTER SETS

Description	Includes	Part No.	Price	
6 Piece Set 1" DOC	9/16", 11/16", 13/16", 15/16", 1-1/16", Cutter Case, and 1" Pilot 9/16"-1-1/16"	12-01848		
6 Piece Set 2" DOC	9/16", 11/16", 13/16", 15/16", 1-1/16", Cutter Case, and 2" Pilot 9/16"-1-1/16"	12-01849		
13 Piece Set 1" DOC	7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8" 15/16", 1", 1-1/16", Cutter Case, and1" Pilot 7/16", 1" Pilot9/16"-1-1/16"	12-01850		
13 Piece Set 2" DOC	7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8" 15/16", 1", 1-1/16", Cutter Case, and1" Pilot 7/16"-1/2", 1" Pilot 9/16"-1-1/16"	12-01851		

#### **TENSITRON TRANSDUCERS**

Tensitron's transducers convert a material's tension into a reliable signal that can be used for remote indication, high-speed recording, computer hook-ups, or as input for automatic tension control systems. Note: A Signal Conditioner is needed to provide the necessary excitation, amplification, signal conditioning, calibration functions, display/readout and other options necessary to operate strain gaged transducers. Attention: Tensitron products may not be cancelled or returned.



# TENSITRON FIBER AND WIRE TRANSDUCERS

Model No.	Description	Tension Range	Part No.	Price
E-090-00	Single Roller Low Force Load Cell	1 - 100 lb.	12-05002	
E-091-00	3 Roller Low Force Load Cell	1 - 100 lb.	12-05003	
E-095-01	Notched Beam Transducer	10 - 1,000 lb.	12-05005	
E-095-03	3 Roller Notched Beam Transducer	10 - 1000 lb.	12-05006	
E-415-002	Small Space Transducer with Single Roller	5 - 5,000 g	12-05011	-
F-1806	Platform Mounted Fiber Transducer	5 - 5,000 g	12-05013	-
FT-107	Small Space Fiber Transducer	5 - 5,000 g	12-05014	
FT-107-TIS	Small Space Fiber Transducer - Titanium	5 - 5,000 g	12-05015	
FT-116	Low Profile 3 Roller Sensor	5 - 5,000 g	12-05016	
FT-117	Single Roller Sensing Beam	5 - 5,000 g	12-05017	



#### **TENSITRON WEB AND BELT TRANSDUCERS**

Model No.	Description	Tension Range	Part No.	Price
4260	Single Roller Web Transducer.	2-200 lb.	12-05001	
E-091-02	Low Force Load Cell with Cyindrical Rollers	1-100 lb.	12-05004	
E-095-04	Notched Beam Transducer with Cylindrical Roller.	25-250 lb.	12-05007	
E-200-00	Cantilever Transducer	1-25 lb.	12-05008	
E-202-00	Pillow Block Load Cell Transducer	25-1,000 lb.	12-05009	
E-210-00	S Column Transducer	5-250 lb.	12-05010	
E-415-003	Small Space Transducer with 3 Rollers	5-5000 g.	12-05012	



#### OMEGA-NEWPORT INFCS TRANSDUCER SIGNAL CONDITIONERS

Model No.	Description	Part No.	Price
INFCS-000 B	Infinity Basic Signal Conditioner, 115 VAC	12-05023	
INFCS-001 B	Infinity Basic Signal Conditioner, 115 VAC Analog Out	12-05024	
INFCS-010 B	Infinity Basic Signal Conditioner, 115 VAC Dual 5A Relays	12-05025	
INFCS-011 B	Infinity Basic Signal Conditioner, 115 VAC Analog Out & Dual 5A Relays	12-05027	
INFCS-100 B	Infinity Basic Signa Conditioner, 230 VAC	12-05028	
INFCS-101 B	Infinity Basic Signal Conditioner, 230 VAC Analog Out	12-05029	
INFCS-110 B	Infinity Basic Signal Conditioner, 230 VAC Dual 5A Relays	12-05030	
INFCS-111 B	Infinity Basic Signal Conditioner, 230 VAC Analog Out & Dual 5A Relays	12-05031	
INFCS-411 B	Infinity Basic Signal Conditioner, 10 to 30 VDC Analog Out & Dual 5A Relays	12-05032	

TO